

36 Sandringham Avenue, Thornton NSW 2226 Phone: 02 4028 6155 www.abovebeyondconcepts.com.au

AUSTRALIA & NEW ZEALAND STANDARDS APPROVED SPEED HUMP

Ideal for traffic and pedestrian safety in shopping centres, multi-level car parks, commercial driveways, service stations, schools and hospitals where there is a requirement to further reduce the speed of vehicles to 30km/h or less.

Features

- Speed Hump Complies with the Australian/New Zealand current standard AS/NZS 2890.1:2004
- Manufactured from TUFF long-lasting UV Stabilised Linear Low-Density Polyethylene [LLDPE]
- Our Australian made speed hump is manufactured from locally made raw materials
- Yellow modules & End Caps are UV treated against fading and will stay Yellow for 10 years



- Two sizes available, 60mm and the SUPA TUFF 70mm size Speed Hump
- Checkered plate design to prevent slipping
- · Lightweight with amazing strength
- Reinforced 12mm fixing hole to take your preferred fastening & 30mm washer
- We guarantee our 60mm & 70mm Standards Approved Speed Hump for 10 years

| PRODUCT CODE | LENGTH | WIDTH | HEIGHT | WEIGHT | FIXING |
|--------------|--------|-------|--------|--------|---|
| CSH60MY | 250mm | 360mm | 60mm | 1.6kg | 2 x 12mm fastening holes with a 30mm rebate |
| CSH60MB | 250mm | 360mm | 60mm | 1.6kg | 2 x 12mm fastening holes with a 30mm rebate |
| CSH60ECY | 200mm | 360mm | 60mm | 0.8kg | 2 x 12mm fastening holes with a 30mm rebate |
| CSH60ECB | 200mm | 360mm | 60mm | 0.8kg | 2 x 12mm fastening holes with a 30mm rebate |
| | | | | | |

60mm STANDARDS APPROVED SPEED HUMP 250MM MODULES

| 70mm STANDARDS | APPROVED SI | PEED HUMP | 250MM MODUL | .ES |
|----------------|--------------------|-----------|-------------|-----|
| | | | | |

| PRODUCT CODE | LENGTH | WIDTH | HEIGHT | WEIGHT | FIXING |
|--------------|--------|-------|--------|--------|---|
| CSH70MY | 250mm | 385mm | 70mm | 1.8kg | 2 x 12mm fastening holes with a 30mm rebate |
| CSH70MB | 250mm | 385mm | 70mm | 1.8kg | 2 x 12mm fastening holes with a 30mm rebate |
| CSH70ECY | 212mm | 385mm | 70mm | 1.0kg | 2 x 12mm fastening holes with a 30mm rebate |
| CSH70ECB | 212mm | 385mm | 70mm | 1.0kg | 2 x 12mm fastening holes with a 30mm rebate |

Fastening Options

 M16 12mm Drop-In wedge anchor with 30mm washer for fixing to concrete or M12 200mm Asphalt Spike for fixing to asphalt/bitumen over base course. Speed Hump Fixing Kit suitable for both concrete and asphalt/bitumen.

70mm STANDARDS APPROVED SPEED HUMP 250MM MODULES

| PRODUCT CODE | FIXING |
|----------------|--|
| WEDGE ANCHOR | M16 x 12mm Drop-In wedge anchor with 30mm washer for fixing to concrete |
| SHFK4 | Speed Hump Fixing Kit, [4 x pcs] M16 x 100mm Nylon plug wit M10 x 100mm screw bolt and 30mm washer Suitable for both concrete and asphalt/bitumen. |
| ROAD SPIKE 200 | M12 x 200mm Asphalt Spike for fixing to asphalt/bitumen over base course |