



LJ-2950 Product Specifications

Engine	350 Hp (261 kW)
Crusher Speed	280 rpm
Feed Opening	50" (1270mm) x 29" (735mm)
Minimum Opening	2" (51mm) *Note Applications
Maximum Opening	7" (175mm) (peak to peak)
Hopper (LXW)	17' - 8" (5374mm) x 12' - 3" (3732mm)
Stockpile Height Main Conveyor	13' - 11" (4250mm)
Main Conveyor Belt Width	48" (1200mm)
Weight	112,435 lbs (51,000 kg)

LJ-SERIES

JAW CRUSHER

The Lippmann LJ-Series are some of the most versatile crushers on the market, boasting the widest jaw in the category along with innovative designs to deliver maximum throughput and production. The LJ-Series delivers industry leading jaw speed, teamed with enhanced die angles, to bring better reduction and material processing to a variety of applications.



PRODUCT FEATURES

- + Jaw with reversible hydrostatic drive, reversible jaw plates, and fully hydraulic closed side setting (CSS) adjust jaw
- + Longer fixed jaw die for more capacity and deeper nip angle deliver better jaw die utilization
- + Enhanced jaw speed leads to better reduction and product being processed faster through the crushing chamber
- + Folding hopper mounted over vibrating pan feeder with integral grizzly pre-screen
- + Cheek plates and flywheels are heavier and balanced for increased efficiency
- + Extended main conveyor as standard, giving large stockpile capacity. Conveyor lowers and raises hydraulically
- + User friendly waterproof and dustproof control panel allows monitoring of pressures, fluid levels, and fuel consumption
- + Track mobile
- + Optional magnet enables magnetic material separation from the source material

LJ-2745 Product Specifications

Engine	350 Hp (261 kW)
Crusher Speed	300 rpm
Feed Opening	45" (1140mm) x 27" (688mm)
Minimum Opening	2" (51mm) *Note Applications
Maximum Opening	6.25" (157mm) (peak to peak)
Hopper (LXW)	14' - 10.2" (4530mm) x 9' - 10" (3000mm)
Stockpile Height Main Conveyor	12' - 8.7" (3880mm)
Main Conveyor Belt Width	42" (1050mm)
Weight	96,783 lbs (43,900 kgs) inc. magnet & side conveyor

LJ-2440 Product Specifications

Engine	225 Hp (166 kW)
Crusher Speed	300 rpm
Feed Opening	40" (1016mm) x 24" (610mm)
Minimum Opening	2" (51mm) *Note Applications
Maximum Opening	6.15" (156mm) (peak to peak)
Hopper (LXW)	13' - 8.5" (4180mm) x 6' - 9" (2064mm)
Stockpile Height Main Conveyor	11' - 4.2" (3458mm)
Main Conveyor Belt Width	36" (900mm)
Weight	76,280 lbs (34,600 kgs) inc. magnet & side conveyor

LJ-2035 Product Specifications

Engine	218 Hp (162 kW)
Crusher Speed	300 rpm
Feed Opening	35" (890mm) x 20" (500mm)
Minimum Opening	1.6" (40mm) *Note Applications
Maximum Opening	4.3" (110mm) (peak to peak)
Grizzly Feeder	82.8" (2102mm) x 166.5" (4230mm)
Stockpile Height Main Conveyor	9' - 10" (3006mm)
Main Conveyor Belt Width	36" (900mm)
Weight	52,580 lbs (23,850 kgs) inc. magnet & side conveyor

Sold and serviced by:



LJ-SERIES
POWERFUL JAW CRUSHERS

Lippmann-Milwaukee Inc.
3271 E Van Norman Avenue
Cudahy, WI 53110-0586
(800) 648 0496 (414) 744-2565
Fax: (414) 744-2565
lippmann-milwaukee.com

The information contained in this literature is meant to be general in nature and is not intended to be used for specific application, construction, or installation purposes. Please note that machine capacities, settings, and other application considerations can vary from the information contained in this literature, depending on the material being crushed, moisture, feed sizes, other materials in the feed, etc. As a result, no warranty of any kind, either expressed or implied, is extended with the information contained in this literature. Lippmann Milwaukee, Inc. expressly reserves the right to change specifications or designs without prior notice or obligation.