



960 RADIAL STOCKPIILER



60ft / 18m Conveyor high quality wheeled stacker with a 900mm wide, 3 ply toughened belt and hydraulic drive as standard. Designed for applications where stockpiling is required after a mobile or stationary crusher, screening or sand washing plant. With fast set up time from arrival on site, the 960 Radial stockpiler can be handling material in no time, for effective production on your job site.

CONVEYOR

Belt Widths	900mm
Belt Length	18m Drum Centres
Plain Belt	EP500 / 3ply
Conveyor Side Section	Modular 5mm Folded Steel Plate
Hydraulic Drive	OMV500
Head Drum	276mm dia. Fully Lagged
Tail Drum	250mm dia. Self Cleaning Spoke
Drum Bearings	60mm HD Centralized Greasing
Belt Tension/Tracking	500mm Adjustment Head+Tail
Centre Rollers	102mm dia. w/20mm Shafts at 400mm Centres <small>(replaceable without removing belt)</small>
Centre Roller Mounts	5mm Folded Sides
HD Return Rollers	100mm dia. with 20mm Shafts at max. 300mm Centres
Skirting Rubber	entire Length of Feed Section
HD Belt Scraper	20mm thick Polyurethane fitted at Conveyor head

Centralised Grease Points

Direct Feed Collection Hopper

POWER UNIT

- CAT 403D-15 (25kW / 33.7HP) Diesel /Hydraulic
- Fuel & Hydraulic Tank
- Hydraulic Raise and Lower on Conveyor
- Hydraulic 2-bank Valve for Raise/Lower/Drive of Conveyor
- Control Valve

CHASSIS

- Constructed out of Box Section
- Galvanised Inner Extension Arms
- Radial Axle with Galvanised Inner Extension Arms
- 6 stud Stub Axle w/ Floatation type Pneumatic Tyres
- Weight Point with Pivot Point
- Tow Bar

TRANSPORT

Length	12550mm
Height	3090mm
Weight	3200kg approx.