



FEIN Dustex 35 LX AC

Wet / dry dust extractor

Powerful, professional wet/dry dust extractor of dust class L with fully automatic filter cleaning for attachment of various case systems including extensive accessories.

Product number: 9 20 30 060 06 0

Details

- > Tool cases of various systems can be simply positioned on the extraction head and secured.
- > Ergonomic transport of the complete unit, including power tool and extractor, thanks to push bar and case and accessory attachment.
- > Fully automatic filter cleaning (AC) makes the flat fold filter last longer for uninterrupted working.
- > Reliable suction of different types of dirt from liquids to fine dusts.
- > Approval for dust class L.
- > With PES flat fold filter and electronic shut-off for outstanding wet extraction performance.
- > Auto start socket with switch-on delay to avoid power surges.
- > Infinitely variable suction force regulation on the extractor.
- > The 7.5 m mains cable and 4 m hose provide a large working radius.
- > Anti-static function for preventing static charging during work - electrostatically discharging thanks to optional suction hose 3 13 45 120 01 0.

Price includes

- ✓ 1 push bar
- ✓ 1 PES flat fold filter
- ✓ 1 disposal bag
- ✓ 1x 4 m suction hose, diameter 35 mm
- ✓ 1 tool collar with suction force regulation
- ✓ 1 stepped collar
- ✓ 2 suction pipes (metal), 1 combi nozzle with interchangeable inserts, 1 crevice nozzle, 1 suction brush, 1 elbow

Product feature

- ✓ Automatic start/stop
- ✓ Soft start
- ✓ Automatic filter cleaning
- ✓ Antistatic preparation
- ✓ Anti-static function: optional
- ✓ Case storage
- ✓ Dust class: L

Technical data

TECHNICAL DATA

Maximum power input	1,380 W
Air flow	4,320 l/min
Max. vacuum	254 hPa
Tank volume	35 l
Cable with plug	7.5 m
Sound pressure level	67 dB
Weight according to EPTA	14.10 kg

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Uncertainty of measured value KpA	67 dB 2 dB
Sound power level LWA Uncertainty of measured value KWA	81 dB 2 dB
Vibration value 1 α_{hv} 3-way	< 2,5 m/s ²



FEIN

Application examples

