

Operating table for demanding workflow





Improved ergonomics

Grand Promerix has lots of improved details for better ergonomics, for example, hidden, smaller castors and inwards cutout for increased foot space. Human-centric design at its best.



C-Arm access

The renewed slim base gives you perfect C-arm access. Grand Promerix meets even the strictest demands of modern operating theatres easily.



Increased hygiene

Details redesigned with patient safety in mind. New bellows & seat section, among other improvements, make Grand Promerix hygienic and easy to clean.



Fluent Lock™

Our Fluent locking system is both user-friendly and reliable. Connect with one click.

Customized solutions for different kinds of surgical operations



Lifting column

- Height with slide 650–1110 mm
- Height without slide 610–1070 mm



Seat section

- With or without slide



Back section models

- Standard: 40-section + 25-section
- Beach chair
- Kidney bridge
- Eye-ENT



Head sections

- Standard head sections for standard back section
- Special head sections for beach-chair and eye-ENT back sections



Leg sections

Upper leg sections

- 100060240 40-section
- 100060425 25-gynaecologic section
- 100060440 40-gynaecologic section
- 145480 Divided leg section, double joint, short
- 100060484 Divided leg section, 4 sectional
- 100060506 Paediatric section
- 100060204 Light leg section for motorized legs
- 100060201 Light foot rest

Lower leg sections

- 100060250 25-section (upper back and lower leg section)
- 100060465 Lower leg section, incl. 2 x 25-section (1000 60250)
- 100060475 Divided leg section, gas spring assisted
- 100030248 Short Divided leg section, with gas springs
- 100030147 One-piece leg section, with gas springs



Highlights

Improved ergonomic design improves the comfort of the whole surgical team. Comfort leads to concentration, confidence and better co-operation.

That's efficiency.



Technical specifications

Promerix	Non-sliding	Sliding
Length	2100 mm	2100 mm
Width (table top)	540 mm	540 mm
Height adjustment	610–1070 mm	650-1110 mm
Safe working load (SWL)	325 kg	275 kg
Trendelenburg	-35°	-35°
Reverse Trendelenburg	+35°	+35°
Head rest adjustment	-45 - +45°	-45 - +45°
Back section adjustment	-45 — +80°	-45 — +80°
Leg section adjustment	-95 - +70°	-105 - +70°
Castors size	80 mm	80 mm
Frequency	47–63 Hz	47–63 Hz
Input voltage	100-240 VAC	100-240 VAC
Weight	300 kg	325 kg
Longitudinal shift of the table top		410 mm
Lateral tilt	20 - 20°	-25 - +25°
Floor clearance	25 mm	25 mm
Max. lifting capacity	490 kg	490 kg
Product Code	100060000	100060000
Official product name: Promerix		



Read more about our Grand Promerix www.merivaara.com





Merivaara Corp. Lahti, FINLAND Tel. +358 3 3394 611 merivaara@merivaara.com

www.merivaara.com

The status of the information, specifications and illustrations in this publication is indicated by the date of publication. Whilst the greatest care has been taken over its compilation, Merivaara Corp. is not responsible for any errors or omissions. Merivaara Corp. reserves the right to make changes to the technology, features, specifications and design of the equipment and models without notice. Please check the Merivaara website for the latest updated specifications and other information.

All trademarks are the property of Merivaara unless otherwise stated. Patents granted or pending.

© Merivaara Corp. DOC ID: 6164EN-1. Date 06/2019

