

VS150 BIOMEDICAL REFRIGERATOR

Vacc-Safe

Vacc-Safe Medical refrigerators are suitable for storing vaccines, medicines and laboratory products between 2°C and 8°C in pharmacies, hospitals, medical clinics and laboratories.



Self Closing Door

Avoid letting the heat in by accident.



Security

Audible and Visual Alarms. Safety Lock.



Single LED Display

High accuracy single LED displays.



DC Turbo Fan

Decreases noise level by 8% while increasing efficiency.



Lockable

Additional security for pharmaceuticals and samples



USB Data

Built in USB Data Logger. Data can be traced and exported.



High Precision Temperature Control.

Vacc-Safe® vaccine and medical cooling storage enables high precision temperature control and accuracy within 0.1°C giving the utmost confidence that goods are stored with precision. LBA Foaming Technology provides more effective insulation to improve performance and reduce overall energy consumption.



Increased Product Lifespan

Powerful heat dissipation for condenser, heat exchange capacity increase by more than 20% than common copper tube fin condenser. Excellent compressor overheating protection, effectively improving the service life of core parts..

Low-E glass door.

Low-E means 'Low Emissivity' which enables a reduction in the transport of heat or cold through the glass.

Simply put it helps to reduce condensation appearing on the inside of the door when opened.



Improved Cooling Performance.

Patented D+ heat exchange technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability. Enjoy improved cooling performance and a 15% reduction in energy consumption along with reduced noise levels

Item	Model No.	VS150
Product structure data	Temperature Range	2~ 8°C
	Fridge Storage Volume(L)	126L Nett
	Product Dimensions(mm) (wxdxh)	595*615*810
	Interior Dimensions(mm) (wxdxh)	505*467*620
	Packing Dimensions(mm) (wxdxh)	665*675*890
	Net/Gross Weight	43/48
Technical data	Compressor type	Fixed frequency
	Cooling Type	Forced air cooling
	Defrost type	No frost
	Climate Class	N
	Rated Voltage/Frequency(V/Hz)	220V/50Hz
	Rated Power(W)	70
	Rated Current(A)	0.75
	Decibel rating	45
Control	Refrigerant/Amount(g)	R600a/26g
	Temp HI/LOW reset	N
	Sensor Qty	2
	Controller	Microprocessor
Product Performance	Display	LED display
	Temperature Accuracy	0.1 °C
	Temperature uniformity/°C	+/-1°C
Alarms	Sound Alarm	Y
	Light Alarm	Y
	Power Failure Alarm	Y
	Sensor Failure Alarm	Y
	Environment Temperature Alarm	N
	Door ajar Alarm	Y
	High Temperature Alarm	Y
	Low Temperature Alarm	Y
Accessories	Remote Alarm	Y
	USB	Y
	Anti-condensation Door	LOW- E glass
	Lock	Y
	Backup Battery	Y
	Backup Battery Endurance	24h
	Shelves/Drawers Qty	3 Shelves
Cable Port	Y	
Castors/type	N	

