GH7000



GH7000



PORTABLE POWER



Technical

| Model | GH7000 |
|------------------------|-----------|
| Туре | Portable |
| Speed | 3000 RPI |
| Phase/Voltage | 1/240 |
| Frequency | 50 Hz |
| Max power kW | 7.0kW |
| Continuous Output | 8.0kVA |
| Noise Level (dBA @ 7m) | 72 |
| Frame | Extra Lar |
| | |

ble RPM A Large roll frame

Engine

Manufacturer **Engine Model** Туре Starting Fuel Run Time Tank Capacity HP 3000 rpm cont **Cubic Capacity Oil Capacity**

Honda GX390 O.H.V. Recoil start **Unleaded Petrol** 2.6 hr @ 100%, 3.8hrs @60% 6.1 L 8.0 HP 389 Cm3 1.1 L

Alternator

Alternator Brand Туре Harmonic Distortion **Protection Class Insulation Class**

Meccalte Brushless Less than 5% IP 23 Class H

10amp + 15amp switched with thermal overload

Dimensions & Weight

| Length | 76 Cm |
|--------|-------|
| Width | 50 Cm |
| Height | 57 Cm |
| Weight | 80 Kg |
| | |

Options

Outlets

Outlet

Outlets Protection Wheel kits Frames Alternators Long Range Tank

Standard (thermal overload protected), Weather protected IP33 & Weatherproof IP66 RCD/ELCB IP30 or IP66 Two wheel or four wheel Extra large Roll Frames Oversized, Single or Three Phase 15 Litre Capacity

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only.