

Data Cable Multipair Overall Screened – LSZH ENV ALT Range

Product Description

Multi Pair, Tinned Copper Conductors, PE Insulated, Overall Screened with an Aluminium/Polyester Laminated Tape with an Annealed Copper Drain Wire, PVC Sheathed Data Cable

Specifications

Conductor	
Material:	Tinned Copper
Stranding:	Class 2
Standards:	AS/NZS 1125
Insulation	
Material:	PE
Operating Temperature:	90°C
Colour(s):	1:Wht/Blu, 2:Wht/Org, 3:Wht/Grn, 4:Wht/Brn, 5:Wht/Grey, 6:Red/Blue, 7.Red/Org, 8:Red/Grn
Standards:	AS/NZS 3808
Sheath	
Material:	HFS-90-TP (LSZH)
Operating Temperature:	90°C
Colour(s):	Grey, Yellow, Green
Standards:	AS/NZS 3808
Voltage	0.6/1kV as per standard S008 (not to be connected to mains power)

*MOQ may apply



Part No.	Colours	No. Of Pairs	Nom. Area mm ²	Cable O.D. mm	Approx Mass kg/km
ELT7201P-ALT	Yellow	1	0.22	4.4	16
ELT7201P-ALT-GR	Grey	1	0.22	4.4	16
ELT7201P-ALT-GN	Green	1	0.22	4.4	16
ELT7202P-ALT	Yellow	2	0.22	6.0	25
ELT7202P-ALT-GR	Grey	2	0.22	6.0	25
ELT7203P-ALT	Grey	3	0.22	6.5	31
ELT7204P-ALT	Grey	4	0.22	7.0	38
ELT7206P-ALT	Grey	6	0.22	8.8	62
ELT7210P-ALT	Grey	10	0.22	10.8	91
ELT7212P-ALT	Grey	12	0.22	11.2	103



Subject to change without notice