

## *TLT245AT 4500kg 2 Post Hoist*



### Specifications:

- . Rated load: 4500kg
- . Lifting height: 1850mm
- . Initial height: 110mm
- . Lifting time: <50s
- . Lowering time: 20s~40s
- . Passing width:
  - symmetric installation: 2486mm
  - asymmetric installation: 2415mm
- . Overall width:
  - symmetric installation: 3420mm
  - asymmetric installation: 3563mm
- . Overall height: 3840mm
- . Motor power 2.2kw
- . Motor voltage: 3 phase/415V,  
1 phase/240V
- . Working oil pressure: 18MPa
- . Working noise: <75dB (A)

### Features:

- 4500kg Heavy Duty floor clearance symmetric 2 post hoist
- Work Safe Australia, third party engineered and assessed and CE certified
- Single-side manual safety lock
- Single-side manual lowering device , safe and easy operation
- Fully concealed cables and pipes
- Dual hydraulic cylinders drive directly (without chains) makes stable and smooth lifting and lowering
- Wire rope equalization system fores synchronous movement of two carriages and effectively prevents vehicle from tilting.
- 24V low voltage control box (IP54 level) ensures operator's safety
- Cylinder travel limit switch effectively protects cylinder and extends its lifespan
- Hose burst protection valves to avoid damage or injury in the event of hose failure
- Door rubber pad protects car door from being damaged in collision
- More lifting pads with different height meets the requirements for light lorries and SUVs
- Passed 115% dynamic loading test and 150% static loading test
- Asymmetric installation is available with optional kits

### Optional 4x4 adaptors



### Consumable rubber pads

