

Product Datasheet

www.1-light.eu

21 Industrial & Floodlights>The COB LED Project Floodlights Die cast

7050A/G/C



10W COB LED Project floodlight.


IP65 rated for outdoor use.

Complies with standard EN60598-1 and any other specific standards.





Dimensions	



Physical Specification

Item Group	21 Industrial & Floodlights
Family	The COB LED Project Floodlights Die cast
Order Code	7050A/G/C
Colour	Grey
Material	Die Cast
Diffuser Material	Glass
Shape	Rectangular

Length	180mm
Width	180mm
Surface Ceiling	Yes
Surface Wall	Yes
Surface Floor/Ground	Yes



Outdoor	Yes
Adjustable	1 Direction

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	10W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	100cm
F Mark	F
Fitting	
	Constant Current

input Type	
Input Current	300mA
Voltage	32V
Power(Watts)	9,6W
IP Rating	IP65

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	9,6-10,8W



Power Factor	0,95
Constant Current	Yes
300mA	32-36V
Manufacturer	0
Protection	0


Illumination Data

Colour Temperature	4000K
Lumen Output	850lm
Light Efficiency	85lm/W
CRI	70
Beam Angle	80°
Illumination Diagram	

Packing Info

Box Length	22cm
Box Width	22cm
Box Height	21,3cm
Pcs/Carton	6
Barcode	5291889037095
HS Code	9405409900

Energy Label





Warranty	2 Years
Weee Directive	Yes

switch to one light!

Certification & Warranty



