



REINVENT HOW THE WORLD CLEANS

CS16

Walk-behind micro-scrubber

High Productivity for Congested Areas

The CS16 is a compact, reliable, and user-friendly micro-scrubber that provides effective cleaning in tight spaces. Its easy-to-use controls, low-profile design and ergonomic handle provide easy operation. The CS16 is ideal for hard-to-reach spaces in areas such as hospitals, retail stores and offices.



ECO Mode

Reduce noise levels and water consumption while increasing run-time with ECO mode.



Compact Storage

Easy to operate in tight spaces and store in crowded storage rooms. Adjustable handle makes it easy to maneuver and store.



Easy-To-Remove Recovery Tank

Keep dirty water separate from clean water with separate solution and recovery tanks. Plus easily remove tank to for battery access.

Inside the CS16

- 1. Comfortable grip and adjustable handle** for ergonomic operation.
- 2. 3-Stage vacuum motor** for strong water pick-up.
- 3. Big capacity:** 15 L solution tank
16.5 L recovery tank.
- 4. Parabolic squeegee shape tracks** the movement of the machine for excellent water pick-up.
- 5. Brush cover** made out of durable material.
- 6. Simple no-tools, no-touch brush change system.**



CS16 Specifications

FEATURE	SPECIFICATION
Cleaning path	350 mm
Productivity (per hour) Theoretical Max	1,300 m ²
Estimated coverage	950 m ²
Max speed	3.5 km/h
Brush RPM	140
Brush/pad pressure	25 kg
Solution tank capacity	15 L
Recovery tank capacity	16.5 L
Run time standard eco mode (up to hours)*	55 mins 70 mins
Power voltage	24 V
Length x width x height (handle in upright position)	950 x 450 x 1,200 mm
Length x width x height (storage position with handle folded down)	950 x 450 x 665 mm
Weight (without Batteries)	36 kg
Sound level (operator's ear)**	68 dBA 66 dBA (eco mode)

Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.

* Run times are based on Continuous Scrubbing Run Times.

** For CE compliance, sound level is measured as an A-weighted sound pressure level per ISO 11201 and reported in accordance with ISO 4871.

For a demonstration or additional information, call **1800 226 843** or email contactus@tennantco.com

Tennant Australia

Unit 2, 10 Johnston Crescent
Horsley Park NSW 2175
T: 1800 226 843 (FREE CALL)
T: +61 2 9839 9700
www.tennantco.com.au
contactus@tennantco.com

Tennant New Zealand

18 Onslow Ave, Papatoetoe,
Auckland, 2104
T: +64 9 253 9013
F: +64 9 253 9015
www.tennantco.co.nz
contactus@tennantco.com