



# ProODO™

## Handheld Optical Dissolved Oxygen Meter

The new ProODO™ provides traditional YSI quality in a handheld dissolved oxygen instrument with luminescent optical dissolved oxygen (DO) technology. The ProODO utilizes “smart” digital sensor technology which stores calibration data within the sensor. This allows probes to be placed on any ProODO instrument without re-calibration.



The ProODO is a digital signal instrument. Any ProODO cable can be connected and used on any ProODO instrument for the field or in a lab BOD bottle. The luminescent optical probes hold the calibration information internally.

YSI ODO technology reduces the time required calibrating and maintaining sensors while utilizing a user replaceable sensing element that requires approximately an annual replacement. There are no electrodes to clean or solutions to change. Based on usage, calibrations can be stable for up to one year and are stored in each sensor.

Optical technology also increases DO accuracy and eliminates probe fouling by common gases such as hydrogen sulfide.

- Expanded DO range of 0-500% with a response time of T90 in approximately 25 seconds
- Non-consumptive luminescent method eliminates stirring
- Easy to read graphic, backlit display and keypad for use in any lighting condition
- *Designed to fit in standard 300 mL BOD bottles.* An external stir plate may be required to ensure a representative sample.
- Truly field-worthy, impact resistant, IP-67 waterproof case and connectors; rubber over molded, non-slip case, for extra durability and grip
- User-replaceable cables in lengths of 1 to 100-meters; cable management kit included with 4-meter and longer cables
- USB connection allows interaction with powerful desktop Data Manager software
- Stores 2000 data sets (sensor data, date, time, site and user defined information)
- Multiple languages include English, Spanish, French, Italian, Norwegian, Portuguese and German. Asian language support in the future.
- 3-year instrument warranty; 2-year cable and probe warranty

Optical DO™

Pure  
Data for a  
Healthy  
Planet.®



+1 937 767 7241  
800 897 4151 (US)  
www.yssi.com

YSI Environmental  
+1 937 767 7241  
Fax +1 937 767 9353  
environmental@ysi.com

YSI Integrated Systems  
+1 508 748 0366  
systems@ysi.com

SonTek/YSI  
+1 858 546 8327  
inquiry@sontek.com

YSI Gulf Coast  
+1 225 753 2650  
environmental@ysi.com

AMJ Environmental  
+1 727 565 2201  
amj@ysi.com

YSI Hydrodata (UK)  
+44 1462 673 581  
europe@ysi.com

YSI Middle East (Bahrain)  
+973 1753 6222  
halsalem@ysi.com

YSI (Hong Kong) Limited  
+852 2891 8154  
hongkong@ysi.com

YSI (China) Limited  
+86 532 575 3636  
beijing@ysi-china.com

YSI Nanotech (Japan)  
+81 44 222 0009  
nanotech@ysi.com

YSI India  
+91 989 122 0639  
sham@ysi.com

YSI Australia  
+61 7 390 17223  
acorbett@ysi.com

**ISO 9001**  
**ISO 14001**

ProODO and ODO are trademarks and Pure Data for a Healthy Planet and Who's Minding the Planet? are registered trademarks of YSI Incorporated.

©2008 YSI Incorporated  
Printed in the USA 0109 W3-02

CC

YSI incorporated  
Who's Minding  
the Planet?®

## ProODO System Specifications (instrument with cable and probe)

<b>Dissolved Oxygen</b> (% saturation)	<b>Sensor Type</b> <b>Range</b> <b>Accuracy</b>	Optical (dynamic luminescence quenching lifetime detection) 0 to 500% air saturation 0 to 200% air saturation, ± 1% of the reading or ± 1% air saturation, whichever is greater; 200 to 500% air saturation, ± 15% of the reading
	<b>Resolution</b>	0.1% air saturation
<b>Dissolved Oxygen</b> (mg/L)	<b>Sensor Type</b> <b>Range</b> <b>Accuracy</b>	Optical (dynamic luminescence quenching lifetime detection) 0 to 50 mg/L 0 to 20 mg/L, ± 0.1 mg/L or ± 1% of reading, whichever is greater;
	<b>Resolution</b>	20 to 50 mg/L, ± 15% of the reading 0.01 or 0.1 mg/L (auto-scaling)
<b>Temperature</b> (°C, °F, °K)	<b>Range</b> <b>Accuracy</b> <b>Resolution</b>	-5 to 70°C ± 0.2°C 0.01°C
<b>Barometer</b> (mmHg, inHg, mBar, Psi, KPa)	<b>Range</b> <b>Accuracy</b> <b>Resolution</b>	375 to 825 mmHg ± 1.5 mmHg from 0 to 50°C 0.1 mmHg

## ProODO Additional Specifications

<b>Storage Temperature</b>	-20 to 70°C
<b>Size</b>	8.3 cm width x 21.6 cm length x 2.3 cm depth (3.25 in x 8.5 in x 2.25 in)
<b>Weight with batteries</b>	475 grams (1.05 lbs)
<b>Probe Dimensions</b>	19 cm length (7.5 in); 2.4 cm diameter (0.95 in)
<b>Power</b>	2 alkaline C-cells; approximately 80 hours - ambient conditions in manual sampling mode
<b>Cable Lengths*</b>	1- 4- 10- 20- 30- 40- 50- 60- and 100-m; (3.3, 13.1, 32.8, 65.6, 98, 131, 164, 197 and 328 ft)
<b>Connectors</b>	MS (military spec) waterproof with bayonet lock
<b>Warranty</b>	3-year instrument; 2-year cable and probe; 1-year sensor cap
<b>Salinity Input Range</b>	0-70 ppt; manual (automatically compensates for manual input value)
<b>Data Memory</b>	2000 data sets (sensor data, date, time, site and user defined information)
<b>Flow Dependence</b>	None
<b>Typical Response Time</b>	90% in 25 seconds; 95% in 45 seconds
<b>Calibration</b>	DO - one point or two point with a zero % value; barometer - one point
<b>Languages</b>	English, Spanish, German, French, Italian, Norwegian, Portuguese; Asian language support in the future
<b>Certifications</b>	RoHS, CE, WEEE, C-Tick, VCCI, IP-67, 1-meter drop test, Assembled in USA
<b>Connectivity</b>	USB 2.0; communications saddle and USB cable included
<b>Data Management</b>	Data Manager desktop software included; 100 user defined folders and site names
<b>User ID</b>	Optional User ID for data security
<b>Measurement/Logging Modes</b>	Automatic and Manual sampling modes/Continuous and Interval logging modes
<b>GLP Compliant</b>	Yes
<b>Probe/Sensor Materials</b>	The following materials may come into contact with the sampling environment: Xenoy® PBT Polycarbonate blend, Noryl, Stainless Steel, Titanium, Polyurethane, Santoprene, Acrylic, Polystyrene

## ProODO Ordering Information (order items separately)

626281	ProODO Handheld instrument
626320	Replacement sensing element (included with initial probe purchase)
626250-1	1-m probe/cable for DO/temp
626250-4	4-m probe/cable for DO/temp (includes cable management kit)
626250-10	10-m probe/cable for DO/temp (includes cable management kit)
626250-20	20-m probe/cable for DO/temp (includes cable management kit)
626250-30	30-m probe/cable for DO/temp (includes cable management kit)
626250-40	40-m probe/cable for DO/temp (includes cable management kit)
626250-50	50-m probe/cable for DO/temp (includes cable management kit)
626250-60	60-m probe/cable for DO/temp (includes cable management kit)
626250-100	100-m probe/cable for DO/temp (includes cable management kit)

## Accessories Ordering Information (visit yssi.com/accessories)

603075	Soft-sided carrying case
603074	Hard-sided carrying case
603069	Belt clip to attach instrument to belt
063517	Ultra clamp (attach to instrument to secure it to a desk, boat, etc)
063507	Small tripod (attach to instrument to sit on any flat surface)
603062	Cable management kit (included with 4- through 100-m cables)
605978	Cable weight, 4.9 oz, attach to stainless steel probe guard

\* Special order cable lengths up to 100-meters in 10-meter increments available.



603069 belt clip



603062 cable management kit



603075 soft-sided carrying case with ProODO, cable, and accessories