

KITO CX SERIES CHAIN BLOCKS



Applications

- ✓ Used in mining, construction, engineering, power transmission fabrication, manufacturing, processing, marine
- ✓ Ideal for the assembly line, workstation, job site, workshop

Features

- ✓ Available in 250kg, 500kg and 1t.
- ✓ Standard lift height of 2.5 meters for 250kg and 500kg, 3.0 meters for 1t. Optional lift heights available upon request.
- ✓ Ultra compact and lightweight.
- ✓ High-quality aluminum housing with non-protruding bolt.
- ✓ Heat-treated steel frame with bearings for gear and load wheel.
- ✓ Completely sealed brake and gear for added protection.
- ✓ Wide hook openings for easy installation and load attachment.
- ✓ Advanced overload limiter as standard equipment.
- ✓ 1t model is equipped with 'twist checker' for enhanced safety.
- ✓ Corrosion and abrasion-resistant nickel-plated load chain.
- ✓ Guided hook latch with tip supporting structure.
- ✓ Operating temperature from -40°C to +60°C.

Extremely lightweight, ultra-compact and strong performance, this mini chain hoist is suitable for any situation that requires lifting with minimal effort and maximum safety.

Capacity: 250kg to 1T

KITO CX Series Chain Blocks

Specifications

Capacity kg	Part No.	Model	Headroom mm	Standard Lifting Height m	Hand Chain Length (folded) m	Pull to Lift Full Load N	Weight kg	Load Chain Diameter x Chain Falls mm	Load Chain Part No.	Dimensions in mm							
										a	b	c	e	f	g	s	t
250	45377	CX003	217	2.5	2.0	147	2.4	3.2 x 1	44835	88	84	217	37	53	21	32	11
500	40322	CX005	260	2.5	2.0	187	4.5	4.3 x 1	40328	101	102	260	44	66	24.5	35.5	12
1,000	45380	CX010	360	3.0	2.5	193	7.3	4.3 x 2	40328	103	122	360	44	87	29	42.5	15

*Optional lift heights available.

Wide top & bottom hook openings


For easy installation and load attachment

Smart body with non-protruding bolts

Minimises the risk of damaging and operator injury during handling

Heat-treated steel frame

Steel frame with bearing for gear and load wheel.
Ensures stable and safe rotation of gear and pinion shaft



CX003



CX005



Capacity
250kg
Mass
(Net weight) **2.4kg**

Capacity
500kg
Mass
(Net weight) **4.5kg**

Capacity
1000kg
Mass
(Net weight) **7.3kg**

Nickel-plated load chain

Breaking stress of 1000 N/mm²

Corrosion-resistant hand chain

Suitable for outdoor use

Twist checker as standard CX010

Enables a quick and easy check if the chain is twisted

Guided hook latch

with tip-supporting structure

**Light, compact
extremely powerful**