

GH6000



PORTABLE POWER

Technical

Model GH6000 Type Portable Speed 3000 RPM Phase/Voltage 1/240 Frequency 50 Hz Max Output @ 0.8pf 6.0kVA Max Power kW Noise 6.5kW Level (dBA @ 7m) 72

Frame Extra Large roll frame

Engine

ManufacturerHondaEngine ModelGX390TypeO.H.V.StartingRecoil startFuelUnleaded Petrol

Run Time 2.6 hr @ 100%, 3.8hrs @60%

Tank Capacity6.1 LHP 3000 rpm cont8.0 HPCubic Capacity389 Cm3Oil Capacity1.1 L

Alternator

Alternator Brand Meccalte
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

Outlets

Outlet 10amp + 15amp switched with thermal overload

Dimensions & Weight

 Length
 76 Cm

 Width
 50 Cm

 Height
 57 Cm

 Weight
 75 Kg

Options

Outlets Standard (thermal overload protected), RCD +

Weatherproof Outlets (IP66 rated)

ProtectionRCD/ELCB IP30 or IP66Wheel kitsTwo wheel or four wheelFramesExtra large Roll Frames

Alternators Oversized, Single or Three Phase

Long Range Tank 15 Litre Capacity



