

MLB BREAST MILK REFRIGERATOR

NULINE
REFRIGERATION

FEATURES

- Fan Forced System
- Voltage Free Connection
- Door Lock
- Door Ajar Alarms
- Interior LED Lighting
- Automatic Condensate Water Disposal
- Fan Door Switch
- Data Logger included
- Battery Backup for Controller
- Digital Display with Built-in Alarms
- Hi/Lo Readout
- Self-closing Doors

	2°C to 4°C
	29 L 59 L 125 L 300 L
	445w x 458d x 535h 450w x 460d x 875h 595w x 610d x 840h 595w x 611d x 1560h



+61 3 9562 3355
info@nuline.au
7 Longford Court, Springvale VIC 3171
www.nulinerefrigeration.com.au

MLB BREAST MILK REFRIGERATOR

NULINE
REFRIGERATION

MODEL	MLB29G	MLB59G	MLB125G	MLB300G*
Gross Capacity	29 L	59 L	125 L	300 L
External Dimensions in mm (w/d/h including castors or legs)	445 x 458 x 535	450 x 460 x 875	595 x 610 x 840	595 x 611 x 1560
Internal Dimensions in mm (w/d/h)	361 x 205 x 400	390 x 390 x 720	505 x 442 x 625	505 x 442 x 1345
Packed Dimensions in mm (w/d/h including pallet)	500 x 575 x 590	660 x 705 x 910	660 x 705 x 910	660 x 705 x 1630
Gross Weight – kg (packed weight)	30	41	50	77
Net Weight – kg	27	38	46	73
Voltage	240V	240V	240V	240V
Temperature Range	2°C to 4°C	2°C to 4°C	2°C to 4°C	2°C to 4°C
Ambient Temperature Range	10°C to 32°C	10°C to 32°C	10°C to 32°C	10°C to 32°C
Refrigerant	R600	R600	R600	R600
Cooling System / Defrost	Fan Forced / Automatic	Fan Forced / Automatic	Fan Forced / Automatic	Fan Forced / Automatic
Exterior Cabinet Finish	Enamelled Steel	Enamelled Steel	Enamelled Steel	Enamelled Steel
Inner Liner Material	ABS	ABS	ABS	ABS
Door	Glass	Glass	Glass	Glass
Door Hinge	RH	RH	RH	RH
Door Handle	Pull Handle	Pull Handle	Pull Handle	Pull Handle
Type of Controller	Digital	Digital	Digital	Digital
Temperature Display	External	External	External	External
Data Logger	Included	Included	Included	Included
Door Ajar Alarms	Yes	Yes	Yes	Yes
High and Low Readout	Visual / Audible	Visual / Audible	Visual / Audible	Visual / Audible
Remote Alarm Contacts (BMS Connectivity for Alarms only) (BMS Connectivity for Temperatures)	Yes Optional	Yes Optional	Yes Optional	Yes Optional
Port Entry	Yes	Yes	Yes	Yes
Battery Back-Up for Controller	Yes	Yes	Yes	Yes
Power Requirement	10 amp GPO	10 amp GPO	10 amp GPO	10 amp GPO
Watts	125w	125w	145w	145w
Castors	No, Adjustable Levelling Legs	No, Adjustable Levelling Legs	No, Adjustable Levelling Legs	No, Adjustable Levelling Legs
Adjustable Shelves	Yes	Yes	Yes	Yes
Usable Shelf Area in mm (w/d)	2 x 376 x 190	2 x 368 x 271 1 x 376 x 190	2 x 488 x 411 1 x 488 x 276	6 x 488 x 411 1 x 488 x 276
Light	LED	LED	LED	LED

*For low volume use only – No more than 25 openings per hour.

For high use needs please see NHRT.

Nuline Refrigeration reserves the right to alter the specifications without prior notice.