

Customised solutions

Weighing and/or Labelling

Below are examples of special custom-made solutions to meet our clients' specific needs.

Double labelling with just one labeller

LA-3000 automatic labelling system without weighing with dual applicator: it prints two labels with just one labeller, almost simultaneously, one after the other. The foot stand is not included.



Special number of conveyors

LS-4000 automatic weigh-price labeller with non-standard number of conveyors (just 1 conveyor).





Non-standard rollers conveyors

LS-3000 automatic weigh-price labeller with special rollers conveyor for heavy products.



Special combination of labellers

LS-4000 automatic weigh-price labeller with special combination of labellers (one top and one side).

Labeller with tilting head

LS-4000 automatic
weigh-price labeller
with tilting top labeller.

The 45° tilting of the
labeller allows labelling
in different positions.



Double labelling with just one labeller

LS-4000 automatic
weigh-price labeller
with special top
labeller, and a
non-standard number
of consoles (two).

The special top labeller
allows double labelling:
one label over the
other. The dual console
allows you to control
the separate start up of
the labellers.





Special dimensions

LS-4000 automatic weigh-price labeller, with special length labelling conveyor (1,200 mm).



Round, oval or flat products

LS-3000 V automatic weigh-price labeller, with special V-shaped conveyors.

- Special "V"-shaped conveyors with variable angle.
- 1 L1,000 mm infeed conveyor, 1 L800 mm weighing conveyor and 1 L1,000 mm labelling conveyor.
- For products of up to Ø 250 mm and up to 6 kg, and 5 g accuracy (in dynamic weighing). Others, contact us.
- 1 top labeller, direct thermal printing, 3" printhead and pneumatic piston applicator.
- Performance*: 60 labels/minute (with W55 x L55 mm labels and product of up to Ø 250 mm and 2 kg).

* Maximum performance will depend on the size, weight and morphology of the product, as well as on the regularity of the infeed of the products, and the dimensions and characteristics of the label.