



# **H0006 ALUMINIUM RAMP**

## **1800KG CAPACITY/PAIR (900KG/PC)**

### **INSTRUCTION MANUAL**

These loading ramps are intended for use in loading vehicles and machinery with rubber wheels, tyres or tracks on/off trailers and transport vehicles.

**MAXIMUM HEIGHT LIMIT TO GROUND LEVEL : 1300mm**

**MAXIMUM LOAD EVENLY DISTRIBUTED: 1800KG/pair. (900KG/PC)**

#### **1. WARNING**

- 1.1 Never exceed the rated capacity of your ramp.
- 1.2 Never exceed the capacity of a loading surface.
- 1.3 Use caution at all times when loading and unloading.
- 1.4 Only load and unload onto a stable, level surface.
- 1.5 Never stand in the path of equipment or vehicle. Keep bystanders and children away.
- 1.6 Do not leave attached ramps unattended.
- 1.7 Do not step between rungs.
- 1.8 Ramp surfaces will have less traction when wet. Use caution.
- 1.9 The ramp is not a toy. Do not use it as a jump, scaffold, bridge, ladder or anything other than its designed purpose.
- 1.10 Suitable for rubber tyres, wheels or tracks only. Not to be used with steel tracks.

#### **2. MAINTENANCE**

- 2.1 It is the user's responsibility to check the loading ramp and components before each and every use. If the ramp is damaged, it should NOT be used.
- 2.2 Maintain the ramp by regular cleaning.
- 2.3 Take care when lifting heavy objects.