

Disabled Hand Basin



HBDA



Scan QR
to view
installation notes



To order this item please advise:

- Tapware and tap hole details (if required)

Product Info:

- Compliant with disability code AS1428 when installed accordingly
- Highly vandal resistant
- Radius safety fascia reinforced with 25mm bar
- Removable, concealed access panel
- Concealed plumbing & wall fixings
- 40mm waste supplied
- Suits P trap installation
- Optional tapware (see Tapware: Section 11)

Suggested Tapware:

(see Tapware Section: 11 for complete range of options)



TW-9108
Timed Flow Lever
Pillar Tap



TW-MIX-L
Fixed Basin Mounted
Lever Mixer



TW-9110
Euro Basin Mounted
Sensor Tap



TW-9101
Eco Timed Flow
Pillar Tap

INSTALLATION NOTES

- 1) Fixture strength is ultimately determined by the load capacity of the supporting structure (noggins recommended for stud walls) and use of appropriate fixings. 2) Basin is secured to wall via six integrated key hole fixing points. Suggested additional fixings are six threaded rods with nuts and washers or 9mm sleeve anchors for masonry walls (not supplied).
- 3) Remove access panel under basin to fit off plumbing and wall fixings then replace panel. 4) P trap not supplied. An offset bracket is supplied to provide additional support to basin at rear. 5) Consult AS1428 standard before installing to confirm mounting set out requirements are current.

