

PROMINIUM®



PROMINIUM® is a high performance, non-combustible, construction grade solid aluminium panel with a durable coating, making it an exceptional exterior cladding choice. PROMINIUM® is deemed non-combustible when tested to AS 1530.1 in accordance with the BCA/NCC requirements.



BCC approved
non-combustible



AS 1530.1



solid
aluminium



KYNAR 500
PVDF coating



CSIRO
certified



superior CNC,
v-groove & fold
performance



rigid & dent
resistant



extended
durability

Applications

- ✓ Exterior Cladding
- ✓ High Rise Buildings
- ✓ Airport Cladding
- ✓ Fascia
- ✓ Formwork

PROMINIUM® is one of the only Non-Combustible cladding solutions available that meets AS 1530.1. It also delivers superior performance when fabricated, folded and formed.

PROMINIUM® is one of Australia's only Non-Combustible aluminium cladding panels purpose designed for use in new constructions and recladding applications.

Developed and manufactured by PROBOND, PROMINIUM® is a solid aluminium panel which offers exceptional fire performance, dependable servability and a durable long-lasting PVDF finished face. It is a low maintenance solution to add high impact and striking features to create iconic landmarks.

The elevated mechanical properties, outstanding surface flatness and simple fabrication mean PROMINIUM® is perfectly suited to cladding requirements within commercial, residential and high elevation developments.

PROMINIUM® is also an efficient, cost-effective method for transforming older structures - creative, contemporary new looks are easily achieved as PROMINIUM® is ideal for retro-fitting over existing facades.

PROMINIUM® requires minimal maintenance and provides excellent long-term performance making it the first choice for all aluminium cladding projects.

ADVANTAGES OF PROMINIUM

- Non-combustible when tested to AS 1530.1
- Exceptional quality solid aluminium - rigid and dent resistant
- Durable UV resistance and colour retention
- Specify with confidence without compromising aesthetics
- Cost effective, large stock holdings and short lead times



Material

3.0mm, 3003 Series solid aluminium offering superior performance, improved rigidity and excellent processing when CNC cutting and folding.

Paint Finish

The most durable coating available - PPG Kynar 500 PVDF Coating for long-term outdoor durability. Standard PVDF range is Satin Finish.

Protective Film

Designed to protect the panel during transit and installation, the film is clearly marked with the panel type for easy identification.

PROMINIUM AVAILABILITIES

Panel Thickness (mm)	3mm
Weight	8.2 kg/m ²
Standard Sizes (mm)	2500mm X 1500mm, 3200mm X 1500mm, 4000mm X 1500mm

