

# GH5000



## **PORTABLE POWER**

## **Technical**

GH 5000 Model Type Portable Speed 3000 RPM Phase/Voltage 1/240 Frequency 50 Hz 5.0kW Max power kW 0.8PF **Maximum** Output Noise Level (dBA @ 72

7m) Frame Large roll frame

#### **Engine**

ManufacturerHondaEngine ModelGX340TypeO.H.V.StartingRecoil startFuelUnleaded Petrol

**Run Time** 3.0 hr @ 100%, 4.2hrs @60%

Tank Capacity6.1 LHP 3000 rpm cont7.2 HPCubic Capacity337 Cm3Oil Capacity1.1 L

### **Alternator**

Alternator Brand Meccalte
Type Brushless
Harmonic Distortion Less than 5%
Protection Class IP 23
Insulation Class Class H

#### **Outlets**

Outlet 10amp + 15amp switched with thermal overload

## **Dimensions & Weight**

 Length
 76 Cm

 Width
 50 Cm

 Height
 57 Cm

 Weight
 56 Kg

#### **Options**

Outlets Standard (thermal overload protected), RCD +

Weatherproof Outlets (IP66 rated)

ProtectionRCD/ELCB IP30 or IP66Wheel kitsTwo wheel or four wheelFramesExtra large Roll Frames

Alternators Oversized, Single or Three Phase

Long Range Tank 15 Litre Capacity

Start Type Electric Start, Full AMF, Remote Start



