
RL5416

STAINLESS STEEL COMPRESSION CANISTER





RL5416 STAINLESS STEEL COMPRESSION CANISTER



Dimensions

RATED CAPACITY	A	В	C	D	E	F	G	Н
mm								
10-50t	ø89	ø43.8	32	150	32	46.9	39.7	7.5

Order Information

LOAD RATING	PART#
10 t	168082
15 t	168083
20 t	168084
25 t	168085
30 t	168087
35 t	168088
40 t	168089
50 t	168090

Note: Refer to page 233 for load cell mount information

Standard Applications

- Truck Scales
- Railroad track scales
- Heavy capacity tanks and hoppers

Standard Features

- 10 to 50 ton
- Stainless steel construction
- IP69k seal type
- Built-in lightning protection
- Built-in gas charged transient protection

Specifications

Full Scale Output:

2,0 mV/V

Output Resistance:

700 ohms, ± 3

Input Resistance:

800 ohms, ± 3

Material Finish:

Stainless steel

Compensated Temperature:

-10° C to 40° C

Operating Temperature:

-10° C to 70° C

Seal Type:

IP69K

Rated Excitation:

15 V

Insulation Resistance:

>5.000 megohms

Cable Length:

20 m

Cable Construction:

auic P\/(

Cable Color Code:

Red+	Excitation
Black	
Green+	Signal
White	Signal
Yellow+	Sense
Blue	Sense

Warranty

• Two-year limited warranty

Approvals





R60 Class C4

Your Rice Lake Weighing Systems distributor is:

