



SMD LED Industrial High Bay, IP65.

Supplied with non-dimmable LED driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Accessories



050114FB



050116HB





22002

Physical Specification

Item Group	21 Industrial & Floodlights
Family	The Industrial IP65 LED UFO Range Waterproof
Order Code	63200F/C
Colour	Black
Material	Die Cast
Shape	Circular

Height	177mm
Diameter	370mm
Surface Ceiling	Yes
Surface Wall	Yes
Suspended Ceiling	Yes
Indoor	Yes
Outdoor	Yes
Adjustable	No


Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	200W
IP Rating	IP65
Light Source	LED built in
Dimmable	No
Cable Length	200cm
F Mark	


Fitting	
Input Type	Constant Current
Input Current	4000mA
Voltage	49V
Power(Watts)	196W
IP Rating	IP65
Light Source	LED built in

LED Type	SMD 2835
LED Brand	Bridgelux
LED Number	300

Gear

Gear Type	Led Driver
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	144-240W
Power Factor	0,9
Constant Current	Yes
Output	4000mA
Voltage Range	36-60V
IP Rating	IP20
Safety Class	

Illumination Data


Colour Temperature	4000K
Lumen Output	20000lm
Light Efficiency	100lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Weight	5,9Kg
Pcs/Carton	2
Carton Length	40cm
Carton Width	40cm

Carton Height	33cm
Carton Weight	12Kg
Barcode	5291889055051
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	5 Years
Weee Directive	Yes

switch to
one light!

