

Instrumentation Cable Multipair Overall Screened – HV Range (LSZH)

Product Description

Multi Pair, Plain Annealed Copper Conductors, PE Insulated, Overall Screened with an Aluminium/Polyester Laminated Tape with a Tinned Annealed Copper Drain Wire, LSZH Sheathed, UV resistant, Instrumentation Cable

Specifications

Conductor	
Material:	Plain Annealed Copper
Stranding:	Class 2
Standards:	AS/NZS 1125
Insulation	
Material:	PE
Operating Temperature:	70°C
Colour:	Black with white numbered cores White with black numbered cores
Standards:	AS/NZS 3808
Sheath	
Material:	HFS-90-TP (LSZH)
Operating Temperature:	90°C
AS/NZS Material Designation:	5V-90
Colour(s):	Blue
Standards:	AS/NZS 3808
Voltage	0.6/1kV

*MOQ may apply

Part No.	Colour	No. Of Pairs	Nom. Area mm ²	Cable O.D. mm	Approx Mass kg/km
ELT7301PBLU-HV	Blue	1	0.5	5.3	28
ELT7302PBLU-HV	Blue	2	0.5	7.5	51
ELT7501PBLU-HV	Blue	1	1.5	7.0	53



Subject to change without notice