



FED-X S/S Double Door Upright Fridge - XURC1200SFV

Quick Overview

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Integrated door handle for easy cleaning
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes

Description

FED-X S/S Double Door Upright Fridge - XURC1200SFV

- Net Capacity: 1200L
- Cooling System: Fan forced cooling
- Temperature range: -2~+8°C
- Compressor: Cubigel
- Controller: Dixell
- Ambient Temperature: 43°C
- RH: 40%
- Refrigerant: R290
- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Integrated door handle for easy cleaning
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes

2 Years Parts and Labour + 2 Years Parts only Warranty with Product Registration

Your Shipping Specifications

Net Weight (Kg)	167
Width (mm)	1340
Depth (mm)	810
Height (mm)	2000
Packing Width (mm)	1365
Packing Depth (mm)	855
Packing Height (mm)	2070
Power	240V; 10A; 430W