

**PON Power Meter** 



## FTTx PON Power Meter

Testing in the FTTx environment just got easier with Yamasaki's latest piece of PON Test Equipment, the TP40 FTTx PON Power Meter. The TP40 includes FTTH PON testing, 6 Wavelength Optical Power Meter & Visible Fault Identifier all in one unit. This rugged hand held unit includes a removable rubberized boot; bright backlit LDC; auto shut off function, wide measurement range, upstream burst mode, accurate testing and bright flashing VFI.

## For Fiber to the Home (FTTH)

Using signal pass through for minimal disruption to customers the Yamasaki TP40 PON Fiber Optic Power Meter simultaneously measures 1310, 1490, 1550nm with 1310nmm wavelength upstream burst mode for communication with ONT.

LED Pass/Fail/Warning indicators allow for instant assessment of power values. The USB port allow for downloading, saving printing of results, pass/fail threshold modification and self-calibration using the PC software and USB cable included.

Optical Power Meter (OPM)

Six calibration wavelengths 850,100,1310,1490,1550 & 1625nm

## Features:

- -LED pass/Fail/Warning indicators
- Simultaneously measures 1310, 1490, 1550nm
- It can detect Voice, data and video signals
- Software to connect to a PC
- Optical power meter and VFL
- Operation Voltage (V) DC 3.3V  $\sim$  5.5V
- -12 Month Warranty



|        | 2      | $\langle \langle \rangle$ |            |  |
|--------|--------|---------------------------|------------|--|
|        | $\geq$ | <                         | $\succ$    |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        | $\sim$                    |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
| _      |        |                           |            |  |
|        | /      |                           |            |  |
|        | /      |                           |            |  |
|        |        | <                         |            |  |
|        | >      | $\langle \rangle$         |            |  |
|        |        |                           |            |  |
|        |        | /                         |            |  |
|        |        | $\leq$                    |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        | /      |                           |            |  |
|        | <      |                           |            |  |
|        |        |                           | $\nearrow$ |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        | $\checkmark$              |            |  |
| $\geq$ |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        | /      |                           |            |  |
|        | /      |                           | $\geq$     |  |
|        | /      |                           |            |  |
|        |        |                           |            |  |
|        |        | $\langle \rangle$         |            |  |
|        | _      |                           |            |  |
|        |        | /                         |            |  |
|        |        | /                         |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
| _      |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        | $\times$                  |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
| /      |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |
|        |        |                           |            |  |

| Model                        | TP40  |
|------------------------------|---|
| 1310 upstream measurement    |   |
| Pass Zone(nm)                | 1260nm~1360nm                                     |
| MeasurementRange(dBm)        | -40dBm~+10dBm                                     |
| Output power (max)           | 15dBm   |
| lsolation@1490/1550(dB)      | >40dB   |
| Burst mode measurement error | <±0.5dB   |
| 1490 downstream measurement  |   |
| Pass Zone(nm)                | 1470nm~1505nm                                     |
| MeasurementRange(dBm)        | -40dBm~+10dBm                                     |
| Output power (max)           | 15dBm   |
| lsolation@1310/1550(dB)      | >40dB   |
| 1550 downstream measurement  |   |
| Pass Zone(nm)                | 1535nm~1570nm                                     |
| MeasurementRange(dBm)        | -40dBm~+10dBm                                     |
| Output power (max)           | 25dBm   |
| Isolation@(1310/1490nm)      | >40dB   |
| Detector Type                | InGaAs  |
| Optical Connector            | FC/SC/ST Interchangeable/2.5<br>Universal adapter |
| Fiber Type                   | SM 9/125um  |

| Ordering Code: | Wavelength     |
|----------------|----------------|
| TP40           | 1310/1490/1550 |



| More information and details visit | www.yamasakiot.com

Specifications and descriptions are subject to change without prior notice.

| To contact us, please email: | sales@yamasakiot.com