

	HCT-3000	HCT-5000
Maximum testing pressure	3000psi (207 bar)	5000 PSI (345 Bar)
Horsepower	7.5 HP	15 HP / 11 kW
Hydraulic Pump Capacity	20 GPM (76 LPM)	10 GPM (38 LPM) at 60 HZ
Hydraulic Pump Capacity	–	8.3 GPM (32 LPM) at 50 HZ
Power Required	ALL VOLTAGE 50/60HZ/3 Ph	ALL VOLTAGE 50/60HZ/3 Ph
Reservoir capacity	60 Gallons (227 Litres)	60 Gallons (227 Litres)
Features	<p>High pressure hoses with quick disconnects Hose storage rack Liquid filled test gauges Quick disconnect adaptors Shop air adapter for oil removal after testing Low friction caster wheels</p>	<p>High pressure hoses with quick disconnects Hose storage rack Liquid filled test gauges Quick disconnect adaptors Shop air adapter for oil removal after testing Low friction caster wheels</p>
Optional Accessories	<p>Item No. 17103 SAE 61 series flange kit 1/2" Flange set, complete 3/4" Flange set, complete 1" Flange set, complete 1 1/4" Flange set, complete 1 1/2" Flange set, complete 2" Flange set, complete</p>	<p>Item No. 17103 SAE 61 series flange kit 1/2" Flange set, complete 3/4" Flange set, complete 1" Flange set, complete 1 1/4" Flange set, complete 1 1/2" Flange set, complete 2" Flange set, complete **NOTE: May only be used when testing to 3000psi Item No. 17104 SAE 62 Series Flange Kit 1/2" Flange set, complete 3/4" Flange set, complete 1" Flange set, complete 1 1/4" Flange set, complete 1 1/2" Flange set, complete 2" Flange set, complete</p>