



AL58/L5

- » Excellent stability.
- » Excellent wear and cut resistance.
- » Suitable for bad roads of mines, tunnel and construction sites.

| SIZE | TYPE | A SNOW L2 | AE39 L3 | AL36 L3 | AL37 L3 | AL53 L5 | AL53+ L5 | AL55 L5 | AL58 L5 | AL59 L5 | AS50 L5S |
|---------------|------|--------------|------------|------------|------------|------------|-------------|------------|------------|------------|-------------|
| 9.00 R20 ** | TT | | | | | | | | | | ● |
| 12.00 R20 ** | TT | | | | | | | | | | ● |
| 15.5 R25 ** | TL | | | ● | | | | | | | |
| 17.5 R25 ** | TL | ● | | ● | ● | ● | | | | | ● |
| 18.00 R25 ** | TL | | | | | | | | | | ● |
| 20.5 R25 ** | TL | ● | | ● | ● | ● | | | ● | ● | |
| 23.5 R25 ** | TL | ● | | ● | ● | ● | ● | | | ● | ● |
| 26.5 R25 ** | TL | | | ● | ● | ● | | | | ● | ● |
| 29.5 R25 ** | TL | | | | ● | ● | | | | | ● |
| 650/65 R25 * | TL | | ● | | | | | | | | |
| 750/65 R25 * | TL | | ● | | | | | | | | |
| 35/65 R33 ** | TL | | | | | ● | | ● | | ● | |
| 35/65 R33 *** | TL | | | | | ● | | ● | | | |

BRISBANE

28 Ashover Rd
Rocklea
QLD 4106

MELBOURNE

41 Paraweena Dr
Truganina
VIC 3029

SYDNEY

Rear 46 Redfern St
Wetherill Park
NSW 2164

PERTH

8 Glassford Rd
Kewdale
WA 6105

