



AUSTRALIAN BOOM & SCISSOR LIFT

ELEVATING WORK PLATFORM HIRE SOLUTIONS


FREE SITE INSPECTION & QUOTATION
EWP TRAINING COURSES AVAILABLE




PRODUCT GUIDE



SCISSOR LIFTS



BOOM LIFTS



VERTICAL MASTS



3 Lennox Place, Wetherill Park NSW 2164

02 9678 9666

www.abslift.com.au



AUSTRALIAN BOOM & SCISSOR LIFT

The Maxi Range

Only available through

Australian Boom and Scissor Lift Pty. Ltd.

Spec's

Max. Platform height
Platform Dimensions
Safe Work Load
Weight approx.
Power Source

SL 172- 24

17.3m / 57 ft.
6.15m x 2.30m
750 kg
10,600 kg
Deutz Diesel

SL 205-25

20.50m / 67 ft.
7.20 x 2.50m
1,000 kg
14,800 kg
Deutz Diesel

SL 260-25

26.30m / 85 ft.
9.80 x 2.50m
1,000 kg
25,000 kg
Deutz Diesel

Ideal Work Applications:

- ✓ Glazing
- ✓ Cladding
- ✓ Roofing
- ✓ Fire & Sprinkler Installation
- ✓ Air Condition Installation
- ✓ Electrical Installation
- ✓ And much more....



For more information on the Maxi Range

Contact:

Steve Franklyn-Smith

ABS Sales Representative

M. 0435 792 134

T. 02 9678 9666

E. steve@abslift.com.au

Australian Boom and Scissor Boom Lift


www.abslift.com.au

HIRE GUIDE


ELECTRIC SCISSOR LIFTS




5.80m (19ft)



5.76m (19ft)




6.20m (20ft)




Model	S06 - E	Optimum 8 AC	Compact 8
Platform Height	5.80m (19ft)	5.77m (19ft)	6.20m (21ft)
Working Height Approx.	7.80m	7.77m	8.20m
SWL	230kg	230kg	350kg
Platform (Retracted)	1.67 x 0.74m	1.72 x 0.74m	2.30 x 0.80m
Platform (Extended)	2.57 x 0.74m	2.59 x 0.74m	3.22 x 0.80m
Stowed Height, Railing up	2.16m	1.98m	2.00m
Stowed Length / Width	1.86 x 0.76m	1.9 x 0.79m	2.48 x 0.81m
Turning Radius (outside)	1.64m	1.5m	2.38m
Gradeability	25%	25%	23%
Tyres	Non-Marking	Non-Marking	Non-Marking
Power Source	Electric	Electric	Electric
Outriggers (Self levelling)	-	-	-
Weight approx.	1,390 kg	1,590 kg	1,730 kg




6.25m (20ft)



8.00m (26ft)



8.25m (27ft)



Model	Compact 8W	Compact 10 N.1	Compact 10
Platform Height	6.25m (21ft)	8.00m (26ft)	8.25m (27ft)
Working Height Approx.	8.25m	10.00m	10.25m
SWL	450kg	230kg	450kg
Platform (Retracted)	2.30 x 1.15m	2.31 x 0.81m	2.30 x 1.15m
Platform (Extended)	3.22 x 1.15m	3.23 x 0.81m	3.22 x 1.15m
Stowed Height, Railing up	2.14m	2.18m	2.26m
Stowed Length / Width	2.45 x 1.20m	2.49 x 0.81m	2.45 x 1.20m
Turning Radius (outside)	2.50m	2.38m	2.50m
Gradeability	23%	23%	23%
Tyres	Non-Marking	Non-Marking	Non-Marking
Power Source	Electric	Electric	Electric
Outriggers (Self levelling)	-	-	-
Weight approx.	1,950 kg	2,450 kg	2,330 kg


ELEVATING WORK PLATFORM HIRE SOLUTIONS

www.abslift.com.au


HIRE GUIDE ELECTRIC SCISSOR LIFTS CONT.




9.75m (32ft)



10.00m (33ft)



11.85m (39ft)



DID YOU KNOW?


ABS IS A MARKET LEADER IN PROVIDING ONE OF THE MOST DIVERSE RANGES OF SCISSOR LIFT AND BOOM LIFT FLEETS, FOR HIRE IN AUSTRALIA.

Model	GS 3232	Compact 12	Compact 14
Platform Height	9.75m (32ft)	10.00m (33ft)	11.85m (39ft)
Working Height Approx.	11.75m	12.00m	13.85m
SWL	227/113kg	300kg	350kg
Platform (Retracted)	2.26 x 0.81m	2.30 x 1.15m	2.30 x 1.20m
Platform (Extended)	3.18 x 0.81m	3.22 x 1.15m	3.22 x 1.20m
Stowed Height, Railing up	2.43m	2.38m	2.50m
Stowed Length / Width	2.44 x 0.81m	2.45 x 1.20m	2.49 x 1.20m
Turning Radius (outside)	2.13m	2.50m	2.38m
Gradeability	25%	23%	23%
Tyres	Non-Marking	Non-Marking	Non-Marking
Power Source	Electric	Electric	Electric
Outriggers (Self levelling)	YES	-	-
Weight approx.	2,306 kg	2,470 kg	3,175 kg


HIRE GUIDE ELECTRIC SCISSOR LIFTS CONT.




10.80m (36ft)




12.50m (41ft)



12.50m (41ft)



15.30m (50ft)



Model	SL 108-16	SL 125-12	SL 125-18	SL 153-12
Platform Height	10.80m (36ft)	12.50m (41ft)	12.50m (41ft)	15.30m (50ft)
Working Height Approx.	12.80m	14.50m	14.50m	17.30m
SWL	500kg	500kg	1000/750kg	500kg
Platform (Retracted)	3.21 x 1.54m	3.91 x 1.16m	3.91 x 1.78m	3.91 x 1.16m
Platform (Extended)	4.61 x 1.54m	5.41 x 1.16m	5.41 x 1.78m	5.41 x 1.16m
Stowed Height, Railing up	2.72m	3.07m	3.07m	3.26m
Stowed Length / Width	3.50 x 1.56m	4.12 x 1.20m	4.15 x 1.82m	4.15 x 1.20m
Turning Radius (outside)	3.10m	4.29m	4.25m	4.25m
Gradeability	25%	25%	25%	25%
Tyres	Non-Marking	Non-Marking	Non-Marking	Non-Marking
Power Source	Electric	Electric	Electric	Electric
Outriggers (Self levelling)	-	-	-	-
Weight approx.	4,710 kg	6,900 kg	7,400 kg	7,600 kg

ELEVATING WORK PLATFORM HIRE SOLUTIONS


www.abslift.com.au

HIRE GUIDE


DIESEL SCISSOR LIFTS




9.75m (32ft)




10.06m (33ft)




10.15m (33ft)



11.00m (37ft)




13.11m (43ft)




Model	GS 3268 RT	GS 3384 RT	Compact 12 DX	SL 110-20 4WDS	SJ 9243 RT
Platform Height	9.75m (32ft)	10.06m (33ft)	10.15m (33ft)	11.00m (37ft)	13.11m (43ft)
Working Height Approx.	11.75m	12.06m	12.15m	13.00m	15.11m
SWL	454/136kg	1,134kg	450kg	750kg	907kg
Platform (Retracted)	2.51 x 1.55m	3.94 x 1.83m	2.50 x 1.54m	3.25 x 1.93m	4.36 x 1.82m
Platform (Extended)	3.96 x 1.55m	5.34 x 1.83m (6.57D)	3.7 x 1.54m	5.27 x 1.93m	7.50 x 1.82m
Stowed Height, Railing up	2.45m	2.68m (2.00m)	2.55m	2.67m	3.02m
Stowed Length / Width	2.38 x 1.73m	4.88 x 2.13m	3.17 x 1.80m	3.47 x 2.00m	4.50 x 2.30m
Turning Radius (outside)	3.68m	5.94m	3.50m	3.40m	3.33m
Gradeability	30%	50%	40%	35%	40%
Tyres	Rough Terrain	Non-Marking	Non-Marking	Non-Marking	Non-Marking
Power Source	Diesel 4WD	Diesel 4WD	Diesel 4WD	Diesel 4WD	Diesel 4WD
Outriggers (Self levelling)	YES	YES	YES	YES	YES
Weight approx.	4,153 kg	6,243 kg	4,060 kg	5,400 kg	6,804 kg




15.24m (50ft)




15.30m (50ft)




17.20m (56ft)



20.50m (67ft)



26.30m (85ft)




Model	SJ 9250 RT	SL 153-22 4WDS L	SL 172-24 4WDS	SL 205-25 4WDS	SL 260-25 4WDS
Platform Height	15.24m (50ft)	15.30m (50ft)	17.20m (56ft)	20.50m (67ft)	26.30m (85ft)
Working Height Approx.	17.24m	17.30m	19.20m	22.50m	28.30m
SWL	681kg	750/500kg	750/500kg	1000kg	1000kg
Platform (Retracted)	4.27 x 1.88m	4.35 x 2.17m	4.35 x 2.30m	5.30 x 2.50m	6.70 x 2.50m
Platform (Extended)	7.21 x 1.88m	7.20 x 2.17m	6.15 x 2.30m	7.20 x 2.50m	9.80 x 2.50m
Stowed Height, Railing up	3.16m	3.27m	3.45m	4.10m	4.20m
Stowed Length / Width	4.47 x 2.34m	4.56 x 2.26m	4.78 x 2.40m	5.70 x 2.55m	7.15 x 2.55m
Turning Radius (outside)	5.33m	4.53m	4.80m	6.00m	4.50m
Gradeability	25%	35%	30%	25%	35%
Tyres	Non-Marking	Non-Marking	Non-Marking	Rough Terrain	Rough Terrain
Power Source	Diesel 4WD	Diesel 4WD	Diesel 4WD	Diesel 4WD	Diesel 4WD
Outriggers (Self levelling)	YES	YES	YES	YES	YES
Weight approx.	7,407 kg	9,100 kg	10,600 kg	14,800 kg	25,000 kg


HIRE GUIDE ELECTRIC and BI-ENERGY BOOM LIFTS




9.10m (30ft)




10.00m (32ft)
HA 121P




13.00m (42ft)
HA 151P



10.20m (33ft)



14.00m (46ft)




Model	Z30-20	HA121P	HA151P	HR12 4x4	JIBBI 1670 EVO
Platform Height	9.10m (30ft)	10.00m (32ft)	13.00m (42ft)	10.20m (33ft)	14.00m (46ft)
Working Height Approx.	11.00m (36ft)	12.00m (39ft)	15.00m (49ft)	12.20m	16.00m
Horizontal Reach	6.40m (21ft)	6.70m (22ft)	8.50m (28ft)	6.10m	8.50m
SWL	227kg	230kg	230kg	200kg	230kg
Platform Length/Width	1.17 x 0.76m	1.20 x 0.80m	1.20 x 0.80m	1.10 x 0.65m	1.80 x 0.70m
Stowed Height	2.00m	1.99m	2.00m	1.95m	1.99m
Stowed Length / Width	5.10 x 1.19m	5.43 x 1.34m	6.60 x 1.50m	4.1 x 1.6m	5.10 x 1.35m
Turning Radius (outside)	3.00m	2.85m	3.70m	3.40m	2.50m
Turnable Rotation	359°	355°	360°	350°	360°
Gradeability	35%	25%	25%	30%	25%
Tyres	Treaded	Non-Marking	Non-Marking	Non-Marking	Non-Marking
Power Source	Electric	Electric	Electric	Electric	Electric
Weight approx.	6,577 kg	5,910 kg	7,490 kg	3,470 kg	3,850 kg


HIRE GUIDE VERTICAL MASTS




4.75m (15ft)



5.95m (20ft)



10.00m (32ft)















Model	SJ16	Star 8S	MVP100E
Platform Height	4.75m (15ft)	5.95m	10.00m (32ft)
Working Height Approx.	6.75m (20ft)	7.95m	12.00m (38ft)
Horizontal Reach	-	-	-
SWL	227kg	200kg	150kg
Platform Length/Width	0.93 x 0.69m	0.77 x 1.78m	0.60 x 0.69m
Stowed Height	1.99m	1.98m	1.99m
Stowed Length / Width	1.37 x 0.77m	1.4 x 0.79m	1.43 x 0.73m
Turning Radius (outside)	1.40m	-	-
Turnable Rotation	-	-	-
Gradeability	30%	25%	N/A
Tyres	Non-Marking	Non-Marking	Non-Marking
Power Source	Electric	Electric	Electric Push Around
Weight approx.	966 kg	1,150 kg	470 kg

DID YOU KNOW?

ABS IS A MARKET LEADER IN PROVIDING ONE OF THE MOST DIVERSE RANGES OF SCISSOR LIFT AND BOOM LIFT FLEETS, FOR HIRE IN AUSTRALIA.

HIRE GUIDE

DIESEL BOOM LIFTS

	10.40m (34ft) 	10.62m (34ft) 	14.00m (46ft) 	15.30m (50ft) 	18.39m (60ft) 
Model	HA 120PX	Z34-22 4x4	HA16 PX 4x4	HA18 PX 4x4	Z51/30J RT
Platform Height	10.40m (34ft)	10.62m (34ft)	14.00m (46ft)	15.30m (50ft)	15.62m (51ft)
Working Height Approx.	12.40m (40ft)	12.50m (40ft)	16.00m (52ft)	17.30m (56ft)	17.62m (56ft)
Horizontal Reach	6.60m (22ft)	6.00m (22ft)	9.10m (29ft)	10.60m (34ft)	10.60m (36ft)
SWL	230kg	227kg	230kg	230kg	227kg
Platform Length/Width	1.50 x 0.80m	1.42 x 0.76m	1.80 x 0.80m	1.80 x 0.80m	1.83 x 0.76m
Stowed Height	2.20m	2.06m	2.20m	2.20m	2.20m
Stowed Length / Width	5.50 x 1.90m	4.11 x 1.85m	7.15 x 2.30m	7.80 x 2.30m	7.50 x 2.29m
Turning Radius (outside)	3.85m	4.11m	3.75m	3.75m	4.50m
Turnable Rotation	350°	355°	360° Continuous	360° Continuous	360° Continuous
Gradeability	45%	45%	50%	50%	45%
Tyres	Rough Terrain	Rough Terrain	Rough Terrain	Rough Terrain	Rough Terrain
Power Source	Diesel	Diesel	Diesel	Diesel	Diesel
Weight approx.	5,620 kg	4,854 kg	7,000 kg	7,900 kg	7,212kg
	19.38m (63ft) 	19.80m (65ft) 	19.80m (65ft) 	24.38m (80ft) 	26.21m (86ft) 
Model	SJ 63AJ	SJ 45T	SJ 66T	800 AJ	SJ86T
Platform Height	19.38m (63ft)	13.77m (65ft)	20.12m (66ft)	24.38m (80ft)	26.21m (86ft)
Working Height Approx.	21.21m (69ft)	15.77m (71ft)	21.95m (72ft)	26.38m (86ft)	28.21m (92ft)
Horizontal Reach	12.19m	12.12m (36ft)	17.37m (36ft)	15.80m (51ft)	15.80m (51ft)
SWL	227kg	227kg	227kg	227kg	341kg/227kg
Platform Length/Width	2.4 x 0.91m	2.44 x 0.90m	2.44 x 0.91m	2.44 x 0.91m	2.44 x 0.91m
Stowed Height	2.54m	2.39m	2.57m	3.00m	3.00m
Stowed Length / Width	9.14m x 2.44m	8.79 x 2.44m	10.34 x 2.44m	11.13 x 2.44m	12.95 x 2.49m
Turning Radius (outside)	5.31m	5.03m	5.05m	4.42m	7.11m
Turnable Rotation	360°	360° Continuous	360° Continuous	360° Continuous	360° Continuous
Gradeability	45%	50%	50%	45%	45%
Tyres	Non-Marking	Non-Marking	Non-Marking	Rough Terrain	Non-Marking
Power Source	Diesel	Diesel	Diesel	Diesel	Diesel
Weight approx.	9,616 kg	7,100 kg	12,111 kg	15,558 kg	17,550 kg



AUSTRALIAN BOOM & SCISSOR LIFT

Sales Rep: Steve 0435 792 134
For all your hire enquiries

Australian Boom & Scissor Lift Pty Ltd
3 Lennox Place, Wetherill Park NSW 2164

t 02 9678 9666

f 02 9678 9777

e sales@abslift.com.au

w www.abslift.com.au

a ABN 37 080 505 826

SCISSOR LIFT	Platform Height	Stowed height	Stowed Length / Width	SWL	Weight	4WD +Outriggers
Dingli S06-E	5.80m / 19ft	1.98m	1.86 x 0.76m	230kg	1,390 kg	
Optimum 8 AC	5.77m / 19ft	1.98m	1.90 x 0.79m	230kg	1,590 kg	
Compact 8	6.4m / 21ft	2.0m	2.48 x 0.81m	350kg	1,730 kg	
Compact 8 W	6.4m / 21ft	2.14m	2.45 x 1.20m	450kg	1,950 kg	
Compact 10 N.1	8.0m / 27ft	2.18m	2.49 x 0.81m	230kg	2,190 kg	
Compact 10	8.3m / 27ft	2.26m	2.45 x 1.20m	450kg	2,330kg	
Compact 12	9.75m / 33ft	2.38m	2.45 x 1.20m	300kg	2,470 kg	
GS3232 SLF LVL	9.75m / 32ft	2.43m	2.44 x 0.81m	227 / 113kg	2,306 kg	
SJ6832RT	9.75m / 32ft	2.38m	2.38 x 1.73m	454kg	4,153 kg	Yes
12DX	10.15m / 33ft	2.55m	3.17 x 1.80m	450kg	4,060 kg	Yes
SL108-16	10.6m / 32ft	2.72m	3.50 x 1.56m	500kg	4,710kg	
GS3384RT	10m / 33ft	2.68m	4.88 x 2.13m	1,134kg	6,243 kg	Yes
Compact 14	11.85m / 39ft	2.50m	2.49 x 1.20m	350kg	3,175 kg	
SL 125-12	12.5m / 41ft	3.07m	4.12 x 1.20m	500kg	6,900 kg	
SL 153-12	15.3m / 50ft	3.26m	4.12 x 1.20m	500kg	7,600 kg	
SJ 9243 RT	13.11m / 43ft	3.02m	4.50 x 2.34m	907kg	7,158 kg	Yes
SJ 9250 RT	15.24m / 50ft	3.16m	4.47 x 2.34m	681kg	7,407 kg	Yes
SL153-22	15.3m / 50ft	3.29m	4.27 x 2.26m	750 / 500kg	8,900 kg	Yes
SL172-24	17.3m / 57ft	3.45m	4.78 x 2.40m	750 / 500kg	10,600 kg	Yes
SL205-25	20.5m / 67ft	4.10m	5.70 x 2.55m	1000kg	14,800 kg	Yes
SL260-25	26.3m / 85ft	4.20m	7.15 x 2.55m	1000kg	25,000 kg	Yes

BOOM LIFTS	Platform Height	Stowed Height	Stowed Length / Width	SWL	Weight	4WD
Skyjack SJ16	4m / 13ft	1.99m	0.93 x 0.69m	227kg	996 kg	
Star 8s	5.95m / 19ft	1.98m	1.4 x 0.79m	200kg	1,150 kg	
MVP100E	10m / 33ft	1.99m	0.60 x 0.69m	150kg	470 kg	
Z30/20 Knuckle	9.1m / 30ft	2.00m	5.10 x 1.19m	227kg	6,577 kg	
HA12 IP/DC	10.0m / 33ft	1.99m	5.43 x 1.34m	230kg	5,910 kg	
Z34/22 DC	10.5m / 34ft	2.20m	4.11 x 1.85m	227kg	4,854 kg	Yes
HA120 PX			5.50 x 1.90m	230kg	5,620 kg	Yes
HA15 IP	13.7m / 45ft	2.00m	6.60 x 1.50m	230kg	7,490 kg	
JIBBI 1670 EVO	14m / 45ft	1.99m	5.1 x 1.9m	230kg	3,850 kg	Yes
HA16 PX 4WD	14.0m / 46ft	2.20m	7.15 x 2.30m	230kg	7,000 kg	Yes
Z45/25J RT			6.83 x 2.29m	227kg	6,688 kg	Yes
HA18 PX 4WD	15.3m / 50ft	2.20m	7.80 x 2.30m	230kg	7,900 kg	Yes
Z51/30J RT			7.50 x 2.29m	227kg	7,212 kg	Yes
Z60/34	18.4m / 60ft	2.69m	8.15 x 2.46m	227kg	11,800 kg	Yes
SJ63AJ Knuckle	19.38m / 63ft	2.54m	9.14 x 2.44m	227kg	9,616 kg	Yes
S65	19.9m / 65ft	2.74m	9.40 x 2.43m	227kg	12,882 kg	Yes
SJ66 T	20.12m / 66ft	2.57m	10.34 x 2.44m	227kg	12,111 kg	Yes
800AJ Knuckle	24.4m / 80ft	3.00m	11.13 x 2.44m	227kg	15,558 kg	Yes
SJ86 T	26.21m / 86ft	3.00m	12.95 x 2.49m	341kg / 227kg	17,550 kg	Yes

Electric

Electric Vertical Lift

Diesel 4x4

Crawler Telescopic Boom