

C.A.I. Product Distribution System (PDS)

Automated Product Separation Solution

The Product Distribution System (PDS) creates product separation in the downstream direction. Each roller on the PDS rotates faster than the previous, helping separation and eliminating product damage or surges. The PDS is custom built to a variety of line widths and heights ranging from 24 inches to 46 inches wide.

Features & Benefits

- Built to specified line widths and heights
- Stainless steel construction with casters and USDA approved synthetic materials
- Increased throughput due to uniform flow
- Efficient sanitation and maintenance
- Electric drive with VFD
- Hopper is constructed of dimpled material

WEIGHING SYSTEMS







Dimpled Hopper

JBT PROTEIN PROCESSING

BRINE PREPARATION | HOMOGENIZATION | INJECTION

SECONDARY

Takeaway Conveyor

Technical Specifications – JBT CAT PRODUCT DISTRIBUTION SYSTEM (PDS)	
APPLICATION(s):	Product separation for higher throughput and reduced styling efforts
OVERALL UNIT DIMENSION(s):	Variable Heights to meet Line 24" to 46" line Widths Depth – 50"
BELT WIDTH(s):	24-46"
CONVEYOR SPEED:	15-45 ft/min
UTILITIES:	480V 3ph 60Hz

For more information and specifications on JBT CAT products, systems, and services contact your local JBT representative or email cat.sales@jbtc.com

WEIGHING | PORTIONING/TRIMMING | COATING | FRYING & FILTRATION | PROOFING



FURTHER

We're with you, right down the line.™ jbtc.com

Fax: + 66 2 261 4099 infoasia-jbtfoodtech@jbtc.com

Australia

Unit 1, 40 Rivergate Place Murarrie QLD 4172 Australia Phone: 07 3896 6100 Fax: 07 3393 9299 info.au@jbtc.com info.nz@jbtc.com

process-solutions@jbtc.com

John Bean Technologies Australia Limited

info-europe@jbtc.com Latin America JBT

Máq. Equip. Ind. Ltda. Av. Eng. Camilo Dinucci 4605 14808-900 Araraquara São Paulo Brazil Phone +55 16 3301 2000 latinamerica.info@jbtc.com