

### Product Information:

- High performance XL hood-type dishwasher with pre-fitted, easy to install energy savings device (ESD)
- **E-Management:** intuitive and advanced electronic interface
- **PRS System:** break tank, 316 atmospheric boiler, rinse booster pump
- **HD System:** for maximum uninterrupted performance
- **ES System:** energy savings device (ESD)
- Increased capacity with 600x500mm baskets (500x500mm compatible)
- XL Filters robust and additional upper tank scrap filters in stainless steel
- Larger HP vertical self-draining wash pump
- Larger HI FLOW stainless steel wash and rinse arms
- Larger elements in wash tank and boiler
- Four wash cycles 90/120/180 seconds, and 9 minute deep clean
- Green standby function that reduces energy consumption when idle
- Low water consumption of 2.5 litres per cycle, minimising water, energy and detergent use
- Pressed wash tank with rounded corners, for increased hygiene
- Manual lift with fully enclosed rear, 3 spring support
- Automatic drain pump with self-cleaning function
- Built in thermostop, ensures correct rinse temperatures
- Built in detergent and rinse-aid injection
- **18-months parts and labour warranty**



### Included Accessories:

- 1 x glass rack 500x600mm
- 2 x plate rack 500x600mm
- 2 x cutlery basket
- 1 x water inlet hose (length 1.5m)
- 1 x drain hose (length 2m)
- Fitted with 150mm adjustable legs

### Optional Accessories:

- Twin hood system
- Remote interface
- Inlet and outlet benches
- Additional baskets

### Specifications:

|   |                   |
|---|-------------------|
| <b>Model</b>                                  | AH60.42EES        |
| <b>W x D x H (mm)</b>                         | 681 x 793 x 2294* |
| <i>Note: Dimensions do not include handle</i> |                   |
| <b>Weight</b>                                 | 179kg             |
| <b>Packed Dimensions (mm)</b>                 | 770 x 930 x 2254  |
| <b>Packed Weight</b>                          | 198kg             |

|                             |                           |
|-----------------------------|---------------------------|
| <b>Total Connected Load</b> | 14.8kW                    |
| - Convertible to:           | 10.3kW (low power option) |

*Note: Unit can be converted to low power option on site by a qualified electrician. This may affect the output of the unit.*

|                              |  |
|------------------------------|--|
| <b>Electrical Connection</b> | 3Ø+N+E 415VAC / 50Hz<br>(Lead fitted, onsite connection) |
|------------------------------|--|

|                                 |                      |
|---------------------------------|----------------------|
| <b>Water Quantity Per Cycle</b> | 2.5 Litres           |
| <b>Water Connection</b>         | 1.5m Hose / 3/4" BSP |
| <b>Water Inlet Pressure</b>     | 100 - 500KPA         |
| <b>Cold water supply</b>        | 10°C - 25°C          |
| <b>Waste Connection</b>         | 2m Hose / ø20.5mm    |

### Legend:

- A Electrical Connection
- B Water Connection
- C Drain Connection
- D Detergent Connection
- E Rinse-Aid Connection

