

T-ZERO PRO

X-POLE 2 X 30W

The T-ZERO X-POLE is an easy to use solar lighting option for construction site entries, walkways, holding areas, car parks, special events and for security purposes. The X-POLE is an all year round clean, silent and zero emission light tower.

The X-POLE operates in complete silence and is 100% solar with zero CO² emissions, ready for your fleet.



ZERO FUEL

The high efficiency solar panel allows the unit to run with zero fuel consumption



ZERO EMISSIONS

Solar Powered lighting with ZERO emissions and a light output of 480 sqm

PRPOWER

1300 399 499



T-ZERO lighting towers are simple, clean and silent with minimal operation and maintenance costs. Leading to long-term environmental and health benefits, the reduction of running costs and zero emissions.

The X-POLE is equipped with an auto dim sensor which saves battery usage and efficiency of the unit. The lights will be dimmed if there is no movement within the surrounding area. If there is movement detected [e.g. a person walking past] the X-POLE's lights will reach full brightness increasing visibility.

The tower provides 2 x 30w energy efficient LED lamps, capable of illuminating 480m².

This lighting tower is ideal for a wide range of applications including construction, industrial, civil works, rental and government projects.

KEY FEATURES



2 x 30w high efficiency LED lamps illuminating approx. 480m²



Auto dim feature to save battery, only registers when movement is detected



Strong galvanised base and powder coating for harsh environments



15-58 hours of operating time with no fuel costs and minimal maintenance



Simple directional light set up atop easy to use mast



Lamps ignite as the sunsets and will automatically turn off when the sun rises



Zero CO₂ emissions, no sound and no fuel



No replacement of ballasts and capacitors required



Complete stand alone unit, set and forget



No bulbs to replace on LED Lamps and they are protected by a polycarbonate lens (no glass)



Silent operation for reduced noise and added security



Compact design allows transport of up to 20 units simultaneously

T-ZERO^{PRO}

TECHNICAL DATA

LIGHTING & MAST

Type of light	2 x 30w LED
Light output	480m ²
Sensor	Auto Dim
Maximum mast height	8m
Mast lifting system	Manual
Electrical protection rating	IP65
Maximum wind speed	80km/h

Batteries & Solar Panel

Solar Panel Power	200w
Battery Type	Lithium
Batteries Number	1
Power Battery Pack	1024 wh
Run Time (Full Brightness)	15 hours
Run Time (Dimmed)	58 hours
Noise rating	No Noise, 0 dBA

DIMENSIONS, WEIGHT AND FEATURES

Units Per Truck	20
Min/Max (LxWxH)	1115x1110x2390/ 1115x1110x8500mm
Dry weight	400kg

PRPOWER 1300 399 499 sales@prpower.com www.prrpower.com