

# Paxum® PR-360

Paxum Fully Automatic  
Pallet Wrapping Machine

#62155



8 Wrapping  
Programs

250% Power  
Pre-Stretch

Remote Control  
Operation

Digital Touch  
Control Panel

## Features

- Auto film cutting & clamping. Low maintenance demand for mechanical device.
- Remote Control Operation
- 250% power pre-stretch
- Film tension can be adjusted from panel. The digital control system maintains the same tension for different sizes and shape of wrapping objects.
- Enlarged space for easier film threading.
- Adjustable film tension from control panel, via 100% electromagnetic brake.
- Auto film tension – film tension begins after first rotation of pallet.
- Adjustable automatic photocell load height detection.
- Security door and foot guard for user protection.
- E-Go control panel.
- Micro-processor provides 8 different wrapping programs.
- Top and bottom wrapping counter from 0-9 cycles.
- Turntable speed adjustable 1-12rpm, soft start and stop.
- Turntable stops in reset position.
- Chain driven turntable.
- Carriage speed adjustable from 0.5m/min - 6m/min.
- Easy film installation and threading design.

## Functions

- Digital Panel with LED indicator for turntable/carriage speed, tension, wrapping counts and program mode.
- With two main wrapping programs, and three auxiliary programs, you can wrap each pallet to suit your specific needs.
  - Single/Double Wrapping
  - Reinforce/Unstable Object & Top Sheet Wrapping
- Memory setting function.
- Speed adjustment from panel for turntable and carriage.
- Reset and Over Wrapping function.
- Handle operation for turntable and carriage.
- Start/Stop push buttons.
- Large Emergency Stop button.



## Specifications

<b>Production Rate</b>	Max. 30 pallets/hour
<b>Turntable Speed</b>	12RPM
<b>Turntable Diameter</b>	1500mm
<b>Max. Load Weight</b>	2000kgs
<b>Max. Wrapping Height</b>	2300mm
<b>Shipping Weight</b>	400kg
<b>Film Stretch</b>	Power Pre Stretch
<b>Film Stretch Rate</b>	250%
<b>Wrapping Tension</b>	Digital Touch Panel Adjust
<b>Electrical Requirements</b>	110V/220V (50/60Hz) 1.5KW
<b>Photocell Sensor</b>	Standard
<b>Operation Panel</b>	Digital Display and Touch Panel
<b>Structure</b>	Full steel construction
<b>Film Spec.</b>	500mm wide, max outer diameter 250mm, Core Diameter 76mm
<b>Technical Data</b>	Operation Manual
<b>Extra Options</b>	Turntable 1650mm / 1800mm Wrapping Height 2500mm Pneumatic Top Pressure 2500kg Load Capacity 750mm wide Film Carriage Access Ramp Weighing Scales System
<b>Warranty</b>	1 Year

