



	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA		STANDARD			
EXTERNAL DIMENSIONS					
width		450 mm			
depth		535 mm			
height		700 mm			
WEIGHT					
37 kg					
VOLTAGE					
230V 50Hz					
POWER REQUIRED					
3200 W					
WATER HARDNESS					
2-8 °F					
INLET WATER PRESSURE					
200-400 kPa					
CROCKERY DIMENSIONS					
plates diameter		295 mm			
glasses max. height		305 mm			
RACK DIMENSIONS					
400X400 mm					
RACK EQUIPMENT					
2XC121 - 1X10728 - 1X15060					
WASHING CYCLES	(sec)	1<60>	2<90>	3<120>	4<180>
WATER SUPPLY 55°C					
racks/h(*) ⁽¹⁾		60	40	30	20
WATER SUPPLY 10°C					
racks/h(*) ⁽¹⁾		16	16	16	16
WATER CONSUMPTION / CYCLE (water pressure 200kPa)					
1.8 L					
BOILER CAPACITY					
3.4 L					
BOILER HEATING ELEMENT					
2800 W					
RINSING TEMPERATURE (SET)					
85°C					
TANK CAPACITY					
14.5 L					
TANK HEATING ELEMENT					
1250 W					
TANK TEMPERATURE (SET)					
55°C					
PUMP POWER					
400 W (185 L/min)					
DRAIN PUMP (optional)					
25 W h MAX vidange 0.8m (40 L/min ^{***})					
NOISE					
60,6[CF] 61,2[LS] (dB(A)±0.7)					

(*) STANDARD TERMOSTOP

(***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.