

Tug Axis 1T/2T POWERED TUG



(Pictured with Auto-latching hitch—320mm height from ground)

A powerful machine, the Tug Axis is available in one or two tonne towing capacities.

Ideal for transporting medical carts around hospitals, moving heavy specialist equipment or moving heavy trolleys.

Using the tiller handle to tow the tug, the operator is in front of the load, increasing visibility and reducing the risk of collisions.

Powered towing can eliminate push/pull injuries caused by manually moving heavy trolleys or repetitive movements.

See pages 29-31 for hitch options.



Typical applications

Suitable for retail and light industrial towing including airports, factories, warehouses, apartment buildings or large facilities.

Features

Tow capacity	<ul style="list-style-type: none"> • Tug Axis 1T: 1000 kg • Tug Axis 2T: 2000 kg (On flat ground, or with reduced towing capacity on ramps up to 8 degrees.)
Max. speed	Up to 5 km/hour
Speed mode	Three speed control with forward, reverse and emergency stop.
Usability	<ul style="list-style-type: none"> • Turret with turret lock for easy reversing. • Easy to use with quiet, smooth operation.
Hitching	Wide variety of hitches available for easy attachment to trolleys.
Dimensions (L/W/H)	1480/610/852 mm (handle down)
Battery	Two 12V 42Ah MK-gel batteries with 48V smart charger

Safety features

- Intuitive control with standard automatic safety brake, forward and reverse drive.
- Emergency stop and back-off safety buttons.

	ORDER CODE	PRICE (+GST)
Tug Axis 1T (no hitch)	TUGAXIS1TNH	
Tug Axis 2T (no hitch)	TUGAXIS2TNH	
Auto-latching hitch	EDHT1810-024	
Pin hitch (16 mm)	EDHT1313	
Pin hitch (19 mm)	EDHT1316	
Clamp hitch	EDHTCLAMP001	
Groove hitch	EDHTGROOVE001	
Tow ball A-frame hitch	EDHT1810-023	