

Tenso® LST4-19

Battery Powered Strapping
Tool 15mm - 19mm

#61826



**Variable
Tension Speed**

**Full Touch
User Interface**

**One Touch
Favourite Setting**

**Strap Alignment
Indication**

The LST4 combination tool delivers high-speed operation and unparalleled performance for plastic strapping applications. Complete with an ergonomic design and multiple performance enhancing features, the LST4 battery hand tool improves productivity for a wide range of applications – from those that require minimal tension to those in heavy industries.

Features

- Full touch user interface
- Variable tension speed
- Favourite strapping function
- Colour display indication for tool status information
- Strap alignment indication
- Strap dust blow out vent
- Battery cover for battery protection



Accessories




User Interface Cover

For additional protection in harsh environments



Protection Plate

For use on abrasive surfaces



Suspension Bow

For stationary applications



Specifications

Operation Mode	auto/semi/manual	Charging Time	25–35 min
Tension Force Range: Standard	1300–4500 N (290–1000 lbf)	Battery Type (standard)	Bosch Li-Ion 18V, 4.0Ah
Soft	400–1600 N (90–340 lbf)		
Variable Tension Speed Range	0–120 mm/s (4.7 in/s)	Cycles per battery charge	
		Low tension	800
		Medium tension	500
		High tension	300
Weight (incl. battery)	4.3 kg (9.5 lb)		
Dimension (LxWxH)	370 x 143 x 135 mm		
Working Temperature	–10°C to +40°C		
Relative Humidity	up to 90%		
Strap Type	PET (Polyester) PP (Polypropylene)		
Strap Width	15–16, 18–19 mm		
Strap Thickness	0.8–1.3 mm		
Joint Type	Friction Weld Seal		
BATTERY / CHARGER			
Charger Type	Bosch		
Battery Charger Voltage	100 or 110 or 230 V		



▶ See me in action!

Tenso® LST4-19