

PR-200

Semi-Automatic Pallet
Wrapping Machine

#62151



Maximises
Productivity

Auto Height
Detection

Simple & Easy
Operation

Digital Touch
Control Panel

Features

- Adjustable film tension from control panel, via 100% electromagnetic brake.
- Auto film tension – film tension begins after first rotation of pallet.
- Adjustable automatic photocell load height detection.
- Security foot guard for user protection.
- E-Go control panel.
- Top and bottom wrapping counter from 0-9 cycles.
- Turntable speed adjustable 1-12rpm, soft start and stop.
- Turntable stops in reset position.
- Chain driven turntable.
- Carriage speed adjustable from 0.5m/min – 6m/min.

Functions

- Digital Panel with LED indicator for turntable/carriage speed, tension, wrapping counts and program mode.
- With two main wrapping programs, and three auxiliary programs, you can wrap each pallet to suit your specific needs.
 - Single/Double Wrapping
 - Reinforce/Unstable Object & Top Sheet Wrapping
- Memory setting function.
- Speed adjustment from panel for turntable and carriage.
- Reset and Over Wrapping function.
- Handle operation for turntable and carriage.
- Start/Stop push buttons.
- Large Emergency Stop button.

Specifications

Production Rate	Max. 30 pallets/hour
Turntable Speed	12RPM
Turntable Diameter	1500mm
Max. Load Weight	2000kgs
Max. Wrapping Height	2300mm
Shipping Weight	400kg
Film Stretch	Magnetic Brake Stretch
Film Stretch Rate	100%
Wrapping Tension	Digital Touch Panel Adjust
Electrical Requirements	110V/220V (50/60Hz) 1KW
Photocell Sensor	Standard
Operation Panel	Digital Display and Touch Panel
Structure	Full steel construction
Film Spec.	500mm wide, max outer diameter 250mm, Core Diameter 76mm
Technical Data	Operation Manual
Extra Options	Turntable 1600mm / 1800mm Wrapping Height 2500mm Pneumatic Top Pressure 2500kg Load Capacity 750mm wide Film Carriage Access Ramp Weighing Scales System
Warranty	1 Year

