

IRRIGATION SET



GKDC4E



Low Noise
Long Life Engine



Technical Data

Model	GKDC4E
Frequency	50 Hz
Prime Power	4kVA 3.2kW
Phases	240 Volt or 415 Volt

Engine

Brand	Kubota
Type Engine	RK95
Governing	Mechanical
Combustion	Direct Injection
Cooling	Water-cooled
Starting	Electric start
Fuel	Diesel
Fuel Tank Capacity	9.5 L
Fuel Consumption	0.75 Litres @ 75% Load
Power kW (HP)	5.9 (8.0)
No. of Cylinders	1
Cubic Capacity	0.487 Litres
Aspiration	Natural

Alternator

Alternator Brand	Meccalte Dual Bearing
Type Regulation	Compound
Speed	1500RPM
Protection Class	IP 23
Insulation Class	Class H

Build

Base	Open Skid with AV Mounts
Starting	Battery, Battery Leads and Stand
Control Panel	Key Start
Engine / Alternator	Belt Drive

Dimensions and Weight

Length	1.20 Cm
Width	72 Cm
Height	80 Cm
Weight	170kgs

Options

Base	Galvanised Base & Guard
Cover	Weatherproof Canopy
Outlets	Single or Three Phase, IP66
Control Panel	Shutdown protection for Low oil pressure & High Engine Temp
Control Panel	As above + Run Down Clock
Control Panel	As above + Pump Pressure
Control Panel	Pivot Shutdown

The information given in this brochure is the assistance of users and is intended for guidance only. Due to a policy of continuous improvement the company reserves the right to amend details and specification without notice and all information given is subject to the Company's current conditions of sale. Photos are for illustration purposes only