



Stacker

Side stacker "roll off"

ROLL OFF

<u>Dimensions*</u>		<u>Machine*</u>	<u>Package*</u>
Width*	mm	685	800
Depth*	mm	2385	2300
High*	mm	660	850
Weight*	Kg	160	230
Volume*	m ³	1,08	1,56

Max stacked items: 10 Pieces
 Width exit items conveyor: 590 mm
 Input speed items to stack: 72 m/min
 Optional stacker right/left,
 front or rear*
 Very compact: stacking with concealed system

<u>Length folds</u>		<u>Crossfold</u>	
Lanes	Folds	Lanes	Folds
-	-	-	-
-	-	-	-

Optional (to define at the order)

Electrical installation*

Electrical power	kW	0,4 *
Voltage 400V ~3N + T	A	0,5 *
Voltage 230V ~3 + T	A	0,9 *

Pneumatic installation*

Compressed air needed bar	6,5	1080	NI/h
---------------------------	-----	------	------

Livello intensità sonora area

<80 dB(A)

<u>Connections</u>	<u>Compressed air</u>	<u>Electricity</u>	<u>Gas/Steam</u>	<u>Exhaust fume</u>	<u>Exhaust (Steam)</u>
Type	Ø 12 mm	F	-	-	-
X mm	-	-	-	-	-
Y mm	-	-	-	-	-
Z mm	-	-	-	-	-



Heating

Natural gas

Consumption	m ³ /h	-
Power	kW	-

LPG

Consumption	m ³ /h	-
Power	kW	-

Steam (P max 12 bar)

Consumption	Kg/h	-
Power	kW	-

Electrical

Consumption	A	-
Power	kW	-

The technical data can change without advice

rev.04