



<11.5 km
Range per Charge



118 kg
Weight Capacity



100.3 cm
Turning Radius



GO GO®
ULTRAX

Ultra-compact for those on the GO!

Experience worry-free travel with the Go-Go® Ultra X, an ultra-compact scooter designed for effortless disassembly into five lightweight pieces with feather-touch technology. The foldable swivel seat offers a comfortable ride, and conveniently access your belongings within reach with the front basket. Choose between the 3 or 4-wheel configuration, making it an ideal choice for individuals on the go.





Removable Battery Box



Feather Touch Dissassembly



3 or 4 Wheel Option Available

RANGE PER CHARGE (MAX) ^{1,3}	Up to 11 km
MAXIMUM WEIGHT CAPACITY	118 kg
TURNING RADIUS ²	3W: 83.8 cm 4W: 100.3 cm
MAXIMUM SPEED ¹	6.4 km/h
LENGTH & WIDTH ^{2,5}	3W: L: 94 cm W: 49.5 cm 4W: L: 100.3 cm W: 49.5 cm
SEAT TYPE DEPTH & WIDTH (STANDARD)	Compact, foldable D: 43 cm (17") W: 43 cm (17")
SEAT-TO-DECK HEIGHT ²	40 cm - 43.8 cm
SEAT-TO-GROUND HEIGHT ²	55 cm - 60 cm
GROUND CLEARANCE ^{2,4}	6.3 cm at midframe 3.8 cm at motor

OVERALL WEIGHT (NOT INC BATTERY) ^{2,6}	3W: 34.5 kg 4W: 36.3 kg
WEIGHT OF HEAVIEST PIECE ²	3W: 13.4 kg (front section) 4W: 15.4 kg (front section)
SUSPENSION	N/A
3W/4W OPTION	3W and 4W
FRONT TYRES ²	3W: 2" x 8" solid 4W: 2" x 7" solid
REAR TYRES ²	2.5" x 8" solid
BATTERY REQUIREMENTS ⁸	(2) 12AH
BATTERY CHARGER	Off-board, 2A
BATTERY WEIGHT ²	4 kg
COLOUR OPTIONS	■ Red

1. Varies with user weight, terrain type, battery amp hour (AH), battery charge, battery condition and tyre condition. This specification can be subject to a variance of 10%.
2. Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of 3%.
3. Tested in accordance with ANSI/RESNA, WC Vol 2, Section 4 and ISO 7176-4 standards. Results derived from the theoretical calculations based on battery specification and drive system performance. Test conducted at maximum weight capacity.
4. Does not account for anti-tip clearance.
5. Width of base (not including seat).
6. Includes standard seat weight.

NOTE: All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%. Special order seats or non-standard dimensions will not fold-flat and depth-adjustable.