

PRODUCT SPECIFICATIONS FOR AP355



OPERATING SPECIFICATIONS

Standard Paving Range	1.75-3.42 m (5' 9" - 11' 2")
Maximum Throughput Capacity	406 tonnes/hr
Maximum Paving Width	4.6 m
Maximum Paving Speed	64 m/min
Maximum Travel Speed	11 km/h

ENGINE

Engine Model (1)	Cat C3.3B
Engine Power (1)	55 kW

WEIGHTS

Operating Weight - With SE34 VT	8700 kg
Operating Weight - With SE34 V	8500 kg
Shipping Weight - Paver Only	7100 kg

DIMENSIONS

Operating Length	5047 mm
Operating Width	3180 mm
Operating Height - With Canopy	3415 mm
Transport Length	4904 mm
Transport Width	1886 mm

Transport Height - Canopy Retracted	2645 mm
--	---------

Truck Entry Height	547 mm
---------------------------	--------

Truck Entry Width	3150 mm
--------------------------	---------

SERVICE REFILL CAPACITIES

Fuel Tank Capacity	110 l
---------------------------	-------

Cooling System	9 l
-----------------------	-----

Engine Oil	13.2 l
-------------------	--------

Hydraulic Oil Tank	80 l
---------------------------	------

Washdown Spray Tank	28 l
----------------------------	------

AP355 STANDARD EQUIPMENT

OPERATING ENVIRONMENT

Single sliding console

Steering guide

TECHNOLOGY

Product Link™ Elite 6412 (cellular)

POWERTRAIN

Cat® C3.3B, four-cylinder

Cooling fan, variable speed

Mobil-trac undercarriage

ELECTRICAL SYSTEM

750 CCA battery, maintenance-free

85-amp alternator

12-volt charging system

Automotive-type fuse system

Cat® Electronic Technician (Cat ET)

MATERIAL DELIVERY

Material feed sensors, contact

Push-roller, adjustable

SERVICE AND MAINTENANCE

Hydraulic oil, Cat HYDO™ Advanced

Remote access drains

Service repair kits

Sampling ports for Scheduled Oil Sampling

Sight Gauges, engine coolant, hydraulic oil

SAFETY

Alarm, back-up

Horn, warning (front & rear)

Lights, LED Working

Mirror package

AP355 OPTIONAL EQUIPMENT

OPERATING ENVIRONMENT

Canopy

Deceleration pedal

Umbrella

Ventilation system

TECHNOLOGY

Basic Grade Control

Product Link™ 631 Satellite

POWERTRAIN

Ballast, front weights

MATERIAL DELIVERY

Material feed sensors, sonic

Wash-down pump and reel

SERVICE AND MAINTENANCE

Bio-hydraulic oil