

4 CART HIGH-CAPACITY INDUSTRIAL DEHYDRATOR

INDUSTRIAL USE • EASY TO MAINTAIN • FULLY STAINLESS STEEL




Save Set Recipes



CSV Data Export



Completion Cooling Cycle



Uniform Drying Without Rotation



Programmable Staged Drying



DrySync™ Technology



Remote Operational Control



Food-Grade 304 Stainless Steel

MODEL IU04 SPECIFICATIONS

Max Power Rating	22.5 kW	Internal Airflow	8000 ft ³ /min
Avg. Power Rating	12-14 kW	Number of Exhaust Fans	2
Voltage / Frequency	3-Phase / 50-60Hz - 120/208V, 277/480V, 120/240V, 240V, 480V, Custom	Total Carts	4 Cart
Product Dimension (W x H x D)	7' 2.5" x 6' 6.75" x 7' 2.5"	Cart Dimensions	36.25" x 4' 9" x 27.5"
Loading Footprint Required	7' 2.5" x 6' 6.75" x 11' 9.5"	Space Between Trays	1 1/2" - 3 1/8"
Machine Weight	3306 lbs	Total Trays	120 - 240 trays
Temperature Range	Ambient - 300°F or 570°F Upon Request	Tray Dimensions	25" x 18"
Exhaust Air Volume	500 cfm (per Exhaust Fan)	Total Tray Area	375 - 750 sq. ft
Static Pressure Rating	1020 pa (per Exhaust Fan)	Timer	0 - 5000 hours
Product Material	Double walled industrial-grade 304 stainless steel. Insulated with high density aluminum silicate cotton.		