



# TOMRA QV-P IN-LINE QUALITY MEASUREMENT

Interested in a free demonstration with your own product or require more information?

Please contact us directly.

### TOMRA Food EMEA

Research Park Haasrode 1622 Romeinse straat, 20 3001 Leuven BELGIUM

Tel: +32 16 396 396 Fax: +32 16 396 390 food@tomra.com www.tomra.com/food

### TOMRA Food AMERICAS

875 Embarcadero Drive West Sacramento California 95605 U.S.A.

Tel: +1 916 388 3900 Fax: +1 916 388 3901 food.us@tomra.com www.tomra.com/food

### TOMRA Food APAC

Unit 1, 20 Anella Ave, Castle Hill, 2154 NSW AUSTRALIA

Tel: +61 2 8624 0100 Fax: +61 2 8624 0101 food.asia@tomra.com www.tomra.com/food

### TOMRA Food CHINA

1A/E, Rihua Building, No.8, Xinfeng 2nd Road, Huli District, Xiamen, Fujian, 361006 P.R.CHINA

Tel: +86 592 572 0780 Fax: +86 592 572 0779 food.china@tomra.com www.tomra.com/food TOMRA's QV-P in-line analyser can reliably detect the muscle myopathy in single chicken fillets or butterflies. This allows to remove wooden breast fillets from the processing line, ensuring consistent end-user quality.

# **BENEFITS**

Ensuring customer satisfaction by providing consistent quality is the main goal of every processor. The QV-P enables poultry processors to identify quality deviations with regards to the wooden breast syndrome. Removing fillets with this defect from the processing line through the TOMRA QV-P in-line analyser ensures a consistent quality level.


The user determined number of grades and the respective thresholds allow processors to determine and categorize per customer quality requirements.



# **TECHNOLOGY**

TOMRA's unique interactance spectroscopy allows to measure into the fillet and determine the internal composition of the meat. Without harmful radiation, it measures each filet or butterfly and provides feedback to the processing line.

The TOMRA QV-P optical head can easily be installed above existing chicken breast processing lines to allow sorting.





## **PRODUCT INFORMATION**

Product analysed	Fresh chicken filets
Capacity	Up to 240 fillets/min
Housing	IP67, stainless steel
Weigh	307 kg