



**CUSHMAN**



# HAULER® 800X

**MAKE TOUGH JOBS SIMPLE**

The Cushman® Hauler® 800X features a lifted suspension that can navigate the most challenging areas of your course. With a customizable bed and practical accessories, it's designed with the versatility you need to build it your way. If topdressing, spot maintenance and debris management are critical to keeping your course in pristine condition, the Hauler 800X is ready to work.

**LET'S WORK.®**

**13.5HP**  
KAWASAKI  
GAS

**725LB**  
LOAD  
CAPACITY

**48V AC**  
ELECTRIC

**8.4 CU. FT**  
CARGO  
BED




## CUSHMAN® HAULER® 800X



CUSTOMIZABLE CARGO BED



FUNCTIONAL DASH



OPTIONAL HUBCAPS



OPTIONAL FLOOR MOUNT ATTACHMENT

### OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- On-Board Charger (Elec. only)
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Hubcaps
- Ball Hitch Receiver
- Comfort Grip Steering Wheel
- High Altitude Jetting
- (Gas only)
- Fuel Gauge
- Battery Fill System (Elec. only)
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Body Color (Patriot Blue, Forest Green, Ivory, Bright White, Flame Red, Orange, Black, Almond, Matte Black, Safety Yellow, Metallic Charcoal)
- Weather Enclosure
- Cab
- Ball Cage
- ROPS

	ELECTRIC	GAS
<b>BODY &amp; CHASSIS</b>		
<b>FRAME</b>	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat	Welded Steel with E-Shield™ ecoat plus DuraShield™ Powder Coat
<b>BODY &amp; FINISH</b>	Injection Molded TPO (front), Injection Molded PP (rear)	Injection Molded TPO (front), Injection Molded PP (rear)
<b>STANDARD COLOR</b>	Forest Green	Forest Green
<b>DIMENSIONS</b>		
<b>OVERALL LENGTH</b>	110 in (280 cm)	110 in (280 cm)
<b>OVERALL WIDTH</b>	49 in (125 cm)	49 in (125 cm)
<b>OVERALL HEIGHT (WITH CANOPY)</b>	74 in (188 cm)	74 in (188 cm)
<b>WHEEL BASE</b>	65.5 in (166 cm)	65.5 in (166 cm)
<b>FRONT WHEEL TRACK</b>	37.0 in (94 cm)	37.0 in (94 cm)
<b>REAR WHEEL TRACK</b>	38.0 in (97 cm)	38.0 in (97 cm)
<b>GROUND CLEARANCE</b>	5.5 in (14 cm)	5.5 in (14 cm)
<b>CARGO BOX CAPACITY</b>	8.4 cu ft (0.24 m³)	8.4 cu ft (0.24 m³)
<b>POWER</b>		
<b>POWERTRAIN</b>	48 Volt AC Drive	4-cycle, 24.5 ci (401 cc) Cylinder
<b>VALVETRAIN</b>	N/A	Single Cylinder OHV
<b>HORSEPOWER (KW)</b>	8.9 hp (6.6 kW) Peak	13.5 hp (10.1 kW) Exceeds SAE J1940 Std.
<b>ELECTRICAL SYSTEM</b>	48 Volt	Starter/Generator, Solid-State Regulator
<b>BATTERY (QTY/TYPE)</b>	Six, 8-Volt Deep Cycle	One 12-Volt Maintenance Free
<b>KEY OR PEDAL START</b>	Pedal	Pedal
<b>OIL FILTER</b>	n/a	Spin-On
<b>COOLING SYSTEM</b>	n/a	Air Cooled
<b>FUEL CAPACITY</b>	n/a	5.6 Gallon (21.3 L) Tank
<b>DRIVE TRAIN</b>	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
<b>TRANSAXLE</b>	Differential with Helical Gears	Differential with Helical Gears
<b>GEAR SELECTION</b>	Dash Mount Forward-Neutral-Reverse	Forward-Reverse
<b>REAR AXLE RATIO</b>	16.99:1	11.47:1 (Forward) 14.35:1 (Reverse)
<b>PERFORMANCE</b>		
<b>SEATING CAPACITY</b>	2 Person	2 Person
<b>CURB WEIGHT</b>	1122 lb (509 kg) - Standard Batteries	830 lb (376 kg)
<b>BED LOAD CAPACITY</b>	325 lb (147.4 kg)	325 lb (147.4 kg)
<b>VEHICLE LOAD CAPACITY</b>	725 lb (328 kg)	725 lb (328 kg)
<b>SPEED</b>	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)
<b>TOWING CAPACITY</b>	500 lb (230 kg) max	500 lb (230 kg) max
<b>OUTSIDE CLEARANCE CIRCLE</b>	18.9 ft (5.8 m)	18.9 ft (5.8 m)
<b>STEERING &amp; SUSPENSION</b>		
<b>STEERING</b>	Self-Compensating Rack and Pinion	
<b>FRONT/REAR SUSPENSION</b>	Leaf Springs w/ Hydraulic Shock Absorbers	
<b>SERVICE BRAKE</b>	Rear Wheel Mechanical Self-adjusting Drum	
<b>PARKING BRAKE</b>	Self-compensating, Single Point Engagement	
<b>FRONT/REAR TIRES</b>	K500 20 x 8.00 -10 (6 Ply Rated)	

800.241.5855 | ©2018 Textron Specialized Vehicles Inc. All specifications subject to change.

70031-G03