




Solar Pro Flex

Street Light



EarthLight 
TRADE


Industrial & Commercial Lighting
earthlight.com.au

Solar Pro Flex

Street Light

The Solar Pro Flex Street Light offers tough and powerful solar lighting with an adjustable solar panel for optimal coverage and positioning. It features smart controls including a microwave sensor, timer, and dimming options, enhancing efficiency and lifespan. It's sleek design, IP66 & IK08 ratings, and durable materials gives the Solar Pro Flex solar street light protection against harsh weather conditions. Because of The Solar Pro Flex's adjustability, it is the best choice in areas such as streets, pathways and carparks where full solar panel positioning is needed.

- ✓ 2~3 Night Lighting, Even Through Rainy Or Cloudy Weather
- ✓ Removable LiFePO4 Lithium Battery
- ✓ Rounded Design For Better Wind Resistance
- ✓ Built-In Smart Controls Such As Microwave Sensor And Timer Dimming Increase Efficiency
- ✓ Highly Efficient 200 Lumen Per Watt Output
- ✓ The Lamp Body Of The Street Light Opens Easily For Maintenance
- ✓ Mountable On Break-Back Or Fixed Poles At Various Heights



Adjustable Solar Panel for Optimal Positioning



Solar Pro Flex


Specifications

| MODEL | ETG-11FL074 |
|----------------------------|---|
| Power (W) | 60 DC |
| Lumen (Lm) | 12,000 |
| Luminous Efficacy (Lm/W) | 200 |
| Battery | LiFePO4 lithium battery |
| Battery Capacity (Wh) | 230.4 |
| Solar Panel (W) | 90 |
| Solar Panel Dimension (mm) | 820 X 670 x 67 |
| Luminaire Dimension (mm) | 502 X 216 x 106 |
| Solar Panel Weight (Kg) | 7.5 |
| Luminaire Weight (Kg) | 5.2 |
| IP Rating | IP66 |
| Charging Time (H) | 3 |
| Solar Charging Controller | MPPT |
| Lighting | Operates at 30% brightness. Once triggered, it brightens to 100% and remains at 100% until no further motion is detected. |
| CCT | 4000K |
| CRI | Ra70 (optional: Ra80) |
| Beam Angle | R22802 |
| Smart Control | Microwave sensor |
| Operating Temperature | 0°C ~ 50°C |
| Material | Aluminium alloy + polycarbonate optical lens |
| Body Colour | Silver |
| Mounting | Side entry |
| Led Lifespan | 40,000 82,000hrs (I80) 131,000hrs (I70) |
| Warranty | 3 years |




Solar Pro Flex

Dimensions





TRADE



Industrial & Commercial Lighting
EarthLight.com.au

**ILLUMINATE™
BETTER**