



Heat Guns

electronically controlled **hot air tool** HL 1920 E

New Products

Information copy

Expert class. Electronically controlled hot air tool HL 1920 E. A versatile tool for removing and welding sheetings, welding plastics, shrinking on cable sleeves, shaping, soldering, drying, thawing, stripping paint and much more besides. Continuous



Details

Electronic precision. For ambitious DIYers.

The HL 1920 E hot air tool is a very handy all-rounder, quite literally. Because with its optimised centre of gravity, the tool feels perfectly balanced in the hand, making it extremely easy to use one-handedly. Finished to a high standard of quality, the HL 1920 E comes with a life expectancy that's a good 20% longer than that of the model it replaces. The multi-talented tool leaves no doubt: at 2000 watts, the tool generates a temperature of 80 °C to 600 °C which can be regulated by thumbwheel. This makes the HL 1920 E a high-precision tool for numerous jobs about the home and for hobby use. For example, removing and welding sheeting, welding plastics, shrinking on cable sleeves, shaping, soldering, drying, thawing, stripping paint and much more besides.

Benefits: the tool's optimised weight balance makes it particularly easy to use with just one hand. For all STEINEL nozzles. With integrated thermal cut-out to prevent overheating. Powerful 2000 watts, infinitely adjustable from 80 °C to 600 °C. Airflow rate adjustable in three stages (150 / 150-300 / 300-500 l/min.). With hanger. Fine dust filter and HL Scan for measuring temperature at the workpiece are available as accessories.



Technical specifications electronically controlled hot air tool HL 1920 E

European Article Number (EAN) 4007841352103

Dimensions (l x w x h) 253 x 84.5 x 200 mm

Voltage	220 - 230 V, 50/60 Hz
Min. frequency	50 Hz
Max. frequency	60 Hz
Power consumption	2000 W
Min. temperature range	80 °C
Max. temperature range	600 °C
Temperature regulation	Yes
Temperature setting	P00264v001
Min. airflow rate	150 l/min
Max. airflow rate	500 l/min
Airflow regulation	3-stage
Airflow rate	Setting 1: 150 l / min. Setting 2: 150 - 300 l / min. Setting 3: 300 - 500 l / min.
Air volume	500 l/min
Motor	Brush motor
Heating element	Ceramic
Protection class (without earth terminal)	II
Thermostat	No
Thermal cut-out	Yes
Power cord length	2.20 m
Weight	0.84 kg
Model	Folding box
(electronically controlled)	Yes

Application

Removing sheeting, welding plastics, shrinking on cable sleeves, welding sheeting, shaping, soldering, drying, thawing, stripping paint and much more besides



Welding bumpers



Cable stripping



Soft soldering



Paint stripping



Heating rubber



Welding tarpaulins