

**Polar —**  
**PO 3T**  
 Catering



**Technical data**

Gross volume	64 lt
Working temperature	-40+10 °C
Performance from +90°C to +3°C	7 Kg
Performance from +90°C to -18°C	5 Kg
Motor type	Plug-in
Refrigerant	R452A
Refrigeration power	792 W (-10°C / +40°C)
Absorption	700 W
Voltage/Frequency	230V/1~/50Hz

**Refrigeration details**

Refrigeration unit	Condensing unit conceived for better performance. Equipped with thermostatic valve
Refrigerant charge	500 gr
Defrost	Manual by air. The equipment can work for 24 hours avoiding ice formation on the evaporator

## Construction details

---

Product dimensions WxDxH	600x855x460
Packaging dimensions WxDxH	700x900x600
Gross weight	61 Kg
Structure	Stainless steel AISI 304 monocoque
External/Internal material	Inside and outside in stainless steel AISI 304; motor unit compartment in colaminated steel
Door	1 Self-closing door right hinged, not reversible on site
Door gasket	Magnetic and removable, designed to improve insulation and to reduce energy consumption
Feet	AISI 304 stainless steel, height adjustable (80mm-100mm)

## Functions

---

Control panel	Capacitive, simple and intuitive display
Functions	Soft and hard blast chilling, soft and hard blast freezing, automatic end cycle holding, pre-cooling
Probe	Needle probe with automatic recognition of the probe inserted in the food

## Accessories

---

No. included accessories	3 - Pair of runners for GN 1/1 and EN 600x400 mm
--------------------------	--

## Versions

---

Versions	Power supply frequency 60Hz
----------	-----------------------------

**Technical datasheet EN**  
Polar PO 3T Catering  
Updated on 06-04-2022