

	<u>Manufacturer</u> MEIKO Maschinenbau GmbH & Co. KG
	<u>Model no.</u> UPster PF 600
	<u>Product Description</u> Utensil Washing Machine
	<u>Origin</u> Offenburg, Germany

SPECIFICATIONS

Function	<p>Utensil Washing Machine</p> <p>The function of the dishwashing machine is to provide the mechanical action necessary to distribute and direct the detergent solution and rinse waters over, under and around dishes to remove soil. The dishwashing machine must also remove soil-laden waters from the machine. This should be done with the lowest consumption of fresh water, energy and chemical products</p>
Form	<p>Dimension : 820 mmW x 760 (1100) mmD x 1600 (1960) mmH</p> <p>Entry Height : 600 mm</p> <p>Basket Size : 670 x 630 mm</p>
Construction	<ul style="list-style-type: none"> - Heavy duty Double-wall construction with additional insulation and rear cladding as a standard stainless steel 304. Hose proof according to safety standard IP X4 - Wash and final rinse system incl. ascending pipes in stainless steel - Oscillating Reversing wash arms and rotating lateral final rinse system made of stainless steel 304 to guarantee 100% coverage of entire wash tank - Rounded wash tank completely covered with easily removable tank filter sieve - Original MEIKO <i>eco filter</i> system for excellent wash results and less cleaning effort - Maintenance-friendly access to all aggregates - Wash pump with dish & glass protecting soft start - Self-cleaning program, temperature display, electronic control system
Engineering / MEP Ratings	<ul style="list-style-type: none"> - Voltage 400V/3NPE/50Hz - Connecting Load: 12.6 kW

	<ul style="list-style-type: none"> - Nominal Current: 20.1 A - Water pressure: min. 2.5 bar, max. 5 bar - Drain hose DN 22 - Inlet ¾"
Capacity	<ul style="list-style-type: none"> - 3 selectable speeds for 30/15/10 racks/hour - Program cycle 120/240/360 sec - Tank content: 60 litres
Sanitation	<p>Entirely corresponds to the regulations of DIN SPEC 10534 for Commercial dishwashing with one-tank dishwashers and for commercial dishwashing with glass washing machines.</p> <ul style="list-style-type: none"> - Wash tank 60°C – 65°C - Final rinse 80°C – 85°C
Accessories	<ul style="list-style-type: none"> - 1 Basket with rollers BV 67 x 63/1 (670 x 630 mm) - Rear Cladding made of Stainless Steel - Connection kit - Rinse aid dosing unit (option) - Detergent dosing unit (option) - Booster pump (option)
Safety	<ul style="list-style-type: none"> - CE (European Standard) - DIN SPEC 10534
Special Requirement	Water Hardness max. 3°dh or approx. 50 ppm