

## Orange Circular Power Cables - LSZH ENV

### Product Description

2 core + earth, 3 core + earth, 4 core + earth, 0.6/1 kV, Flexible Plain Annealed Copper Conductors, X-HF-90 Insulated, HFS-90-TP Sheathed. Compliance with AS/NZS 5000.1.

### Specifications

<b>Conductor</b>	
Material:	Plain Annealed Copper
Stranding:	Class 5
Standards:	AS/NZS 1125
<b>Insulation</b>	
Material:	X-HF-90
Operating Temperature:	-20°C - 90°C
Colour:	Red, White, Blue, Black and Green/Yellow
Standards:	AS/NZS 3808
<b>Sheath</b>	
Material:	HFS-90-TP (LSZH)
Operating Temperature:	-20°C - 90°C
Colour(s):	Orange (standard) and Blue
Standards:	AS/NZS 3808
Voltage Rating:	0.6/1 kV
<b>Packaging</b>	Usually Timber Drum, Length as Ordered* Plastic Drum for short lengths, usually less than 50mtrs

\*MOQ may apply



Part No.	Colours	No. Of Cores	Nom. Area mm <sup>2</sup>	Earth size per Core mm	Nom Cable O.D. mm	Approx Mass kg/km
ELT2025E-ENV	Orange, Blue	2 + E	2.5	2.5	12.8	195
ELT3025E-ENV	Orange	3 + E	2.5	2.5	13.7	236
ELT4025E-ENV	Orange, Blue	4 + E	2.5	2.5	14.7	280
ELT2040E-ENV	Orange, Blue	2 + E	4.0	2.5	13.5	235
ELT3040E-ENV	Orange	3 + E	4.0	2.5	14.6	293
ELT4040E-ENV	Orange, Blue	4 + E	4.0	2.5	15.8	355
ELT2060E-ENV	Orange, Blue	2 + E	6.0	2.5	14.4	286
ELT3060E-ENV	Orange	3 + E	6.0	2.5	15.6	365
ELT4060E-ENV	Orange, Blue	4 + E	6.0	2.5	17.0	449



Subject to change without notice