



SPECIFICATIONS

- **Screen Size:** 13.3 inches
- **Resolution:** 1920 x 1080 pixels
- **Aspect Ratio:** 16:9
- **Brightness:** 300 cd/m²
- **Contrast Ratio:** 800:1
- **Viewing Angle:** 170° horizontal/170° vertical
- **Touch Capability:** Optional 10-point capacitive touch
- **Input Interfaces:** HDMI, DisplayPort (DP), VGA
- **Output:** 3.5mm earphone jack
- **Power Supply:** DC 7-24V (12V standard)
- **Power Consumption:** ≤12W (12V)



13.3" Industrial Grade Touch Screen Monitor (FA 1330 C-T)

KEY FEATURES

- **13.3" Capacitive Touch Screen:** 10-point touch for interactive applications (optional).
- **Multiple Input Support:** HDMI, VGA, and DisplayPort (DP) for versatile connectivity options.
- **High-Resolution Display:** Supports HDMI 4K at 30Hz for clear video output.
- **Wide Operating System Compatibility:** Works with Windows XP/7/8/8.1/10, Android, Linux, and Mac OS.
- **Brightness and Viewing Angle:** 300 cd/m² brightness with a 170° wide viewing angle, suitable for general use.



- **Location:** APS Technology Australia Pty Ltd, Epping NSW, Australia
- **Email:** info@aps-technology.com.au
- **Website:** www.aps-technology.com.au





SPECIFICATIONS

- **Operating Temperature:** 0°C to 50°C
- **Storage Temperature:** -20°C to 60°C
- **Dimensions:** 320 x 208 x 26.5mm
- **Weight:** 1.15kg
- **VESA Mount:** 75mm



13.3" Industrial Grade Touch Screen Monitor (FA 1330 C-T)

KEY FEATURES

- **On-Screen Menu Settings:** Includes options for adjusting brightness, contrast, saturation, and more, with easy access through shortcut buttons.
- **Customizable Backlight and OSD Features:** Adjustable backlight (0-100%) and OSD rotation (90°, 180°, 270°).

