# Vacc-Safe

# **ULT Freezer**

VS-86L818S 838 Litre

Suitable for storing vaccines, medicines and laboratory products and samples between -40°C and -86°C in pharmacies, hospitals, medical clinics and laboratories.





#### **VIP Plus Insulation.**

Provides up to 30% more storage capacity than a conventionally insulated freezer.



#### **Increased Product** Lifespan.

Dissipates heat 20% more effectively to improve life expectancy of core parts.



## **Multi-layer Silicone** Sealing Structure.

Provides a tight seal between inner and outer door for better insulation.



#### **Touch Screen Control Panel.**

Visual management, real time display, inner temperature, alarms, temperature curves, door open tracking.



### **Improved Cooling** Performance.

Patented Smart-Inverter technology significantly reduces the amount of energy consumed whilst maintaining superior temperature stability.



**Built-In Backup Battery** 



Security



**Touch Screen** Display



**USB Data** 



Lockable

# Vacc-Safe



1175 mm

| -40 to −86°C   |
|----------------|
| 838L nett      |
| 1175x995x1980  |
| 885x720x1310   |
| 1240x1115x2030 |
| 332/401        |
|                |

| Technical data                 |                        |
|--------------------------------|------------------------|
| Compressor Type                | 2x Inverter Compressor |
| Cooling Type                   | Direct Cooling         |
| <b>Defrost Type</b>            | Manual                 |
| Climate Class                  | N                      |
| Rated Voltage/Frequency (V/Hz) | 220V/50Hz              |
| Rated Power (w)                | 2030                   |
| Rated Current (A)              | 9.5                    |
| Decibel Rating (dBA)           | 51                     |
| Refrigerant/Amount (g)         | Mixed                  |

| Control     |                |
|-------------|----------------|
| Sensor Qty  | 3              |
| Sensor Type | NTC            |
| Controller  | Microprocessor |
| Display     | Touch Screen   |

| Product Performance       |       |
|---------------------------|-------|
| Temperature Accuracy      | 0.1°C |
| Temperature uniformity/°C | ≤5°C  |

| Alarms |  |
|--------|--|
| Yes    | Sound, light, power failure, sensor failure,<br>environment temperature, door ajar, high |
|        | temperature, low temperature, remote.  |

| Accessories                     |                      |
|---------------------------------|----------------------|
| USB                             | Υ                    |
| Door Heating                    | Υ                    |
| Lock                            | Υ                    |
| Backup Battery                  | Υ                    |
| <b>Backup Battery Endurance</b> | 15h                  |
| Shelves/ Drawers Qty            | 3 shelves            |
| Cable Port                      | Υ                    |
| Castors/type                    | 4 + 2 Levelling Feet |